

Organizer: Institute of Formal and Applied Linguistics,
Faculty of Mathematics and Physics, Charles University in Prague,
Malostranské nám. 25, 118 00 Prague, Czech Republic,
<http://ufal.mff.cuni.cz/>



Prague Treebanking for Everyone: A two-day tutorial

Tutorial Notes

November 28-29, 2006
Prague, Czech Republic

The tutorial is supported by:



Faculty of Mathematics and Physics
Charles University in Prague
Ke Karlovu 3, 121 16 Praha 2
Czech Republic
<http://www.mff.cuni.cz/>

Czech Society for Cybernetics
and Informatics
Pod Vodárenskou věží 2
182 07 Praha 8 – Libeň
Czech Republic
<http://www.cska.cz/>

Central European Initiative
CEI - Executive Secretariat
Via Genova, 9
34121 Trieste, Italy
<http://www.ceinet.org/>

Open Society Institute
400 West 59th Street
New York, NY 10019
USA
<http://www.soros.org/>

© 2006, Institute of Formal and Applied Linguistics, Faculty of Mathematics and Physics, Charles University, Prague

Electronic version can be obtained via the web:
<http://ufal.mff.cuni.cz/pdt.html>

Preface

Traveling to Prague in autumn 2006 is a great opportunity to enjoy events and meet people behind them which have to do something with computational linguistics. The Institute of Formal and Applied Linguistics organizes the following international events at this time: the Vilém Mathesius Centre Lecture Series 21, the 5th international “Treebanks and Linguistic Theories” conference and, last but not least, the “**Prague Treebanking for Everyone**” tutorial, the notes of which you are visiting now.

The tutorial introduces the Prague Dependency Treebank project, which aims at a complex (mainly) manual annotation of a substantial amount of naturally occurring sentences in continuous Czech texts. The Prague Dependency Treebank has three levels of annotation: morphological, analytical (describing surface syntax in a dependency fashion) and tectogrammatical, which combines syntax and sentence semantics into a language meaning representation, keeping the dependency structure as the core of the annotation structure but adding basic coreferential links, topic/focus annotation, and a detailed semantic labeling of every sentence unit. Several other treebanks having originated in Prague are introduced as well (the Czech Academic Corpus, the Prague Czech-English Dependency Treebank, and the Prague Arabic Dependency Treebank). In addition to the data, all the treebank and data processing tools are discussed in details.

The tutorial is given by nine different speakers from the host institute. Such high number (representing in fact a much higher number of the Prague “treebankers”) reflects the fact that collecting a huge bank of trees is unimaginable without a real teamwork with a strong leadership building on a solid theoretical basis. Fortunately, in case of all Prague treebanks these presumptions are fulfilled.

The speakers’ notes in the tutorial material are arranged in the same order as they are presented during the tutorial. They are accompanied by three colorful solid cards to help the users to become more familiar with morphological tags, analytical functions and tectogrammatical attributes used in the Prague treebanks. Together with them two cd-roms are provided: the PDT 2.0 cd-rom and the CAC 1.0 cd-rom consisting of everything what is included in their original distributions (by the Linguistic Data Consortium and the Charles University Press, respectively) except for the full data.

We wish you to have a wonderful time in Prague!



Jan Hajič

Eva Hajčová

Barbora Hladká

List of Speakers

Name	e-mail address
Jan Hajič	hajic@ufal.mff.cuni.cz
Eva Hajičová	hajicova@ufal.mff.cuni.cz
Jaroslava Hlaváčová	hlava@ufal.mff.cuni.cz
Ondřej Kučera	kucera@ufal.mff.cuni.cz
Jiří Mírovský	mirovsky@ufal.mff.cuni.cz
Petr Pajas	pajas@ufal.mff.cuni.cz
Otakar Smrž	smrz@ufal.mff.cuni.cz
Jan Štěpánek	stepanek@ufal.mff.cuni.cz
Zdeněk Žabokrtský	zabokrtsky@ufal.mff.cuni.cz

Time Schedule

NOVEMBER 28, 2006
Tuesday

09:30-11:00	Part 1 DATA: The Prague Dependency Treebank and the Czech Academic Corpus (<i>Jan Hajič</i>) <ul style="list-style-type: none">• Introduction• Morphology
11:30-13:00	Part 2 DATA (continued): PDT (<i>Jan Hajič</i>) <ul style="list-style-type: none">• Surface Dependency Syntax• "Deep" (Tectogrammatical) Syntax
13:00-14:30	Lunch
14:30-16:00	Part 3 DATA (continued): PDT <ul style="list-style-type: none">• Grammatemes (<i>Zdeněk Žabokrtský</i>)• "Deep" Syntax: topic/focus and deep word order (<i>Eva Hajičová</i>)• Coreference (<i>Eva Hajičová</i>)
16:30-18:00	Part 4 DATA (continued): PDT: Valency (<i>Jan Hajič</i>)

Time Schedule (continued)

NOVEMBER 29, 2006
Wednesday

09:30-11:00	Part 5 TOOLS <ul style="list-style-type: none">• Annotation editors<ul style="list-style-type: none">• m-layer: LAW (<i>Jaroslava Hlaváčová</i>)• [at]-layer, valency lexicon: TrEd (<i>Jan Štěpánek</i>)• Browsers and viewers<ul style="list-style-type: none">• m-layer: Bonito (<i>Jaroslava Hlaváčová</i>)• [at]-layer: Netgraph (<i>Jiří Mirovský</i>)
11:30-12:30	Part 6 DATA: The Prague Mark-up Language (<i>Petr Pajas</i>)
12:30-14:30	Lunch
14:30-16:00	Part 7 TOOLS (continued): <ul style="list-style-type: none">• Automatic processing of data (<i>Jan Štěpánek</i>)• STYX - an electronic exercise book of Czech (<i>Ondřej Kučera</i>)
16:30-18:00	Part 8 DATA: More Prague Treebanks <ul style="list-style-type: none">• Prague Czech-English Dependency Treebank (<i>Jan Hajič</i>)• Prague Arabic Dependency Treebank (<i>Otakar Smrž</i>)

Part 1

DATA:
The Prague Dependency
Treebank
and the Czech Academic Corpus

The Prague Dependency Treebank and Valency Annotation (part 1)



Jan Hajíč
Institute of Formal and Applied Linguistics
School of Computer Science
Faculty of Mathematics and Physics
Charles University, Prague
Czech Republic

1

VnIC Tutorial: The Prague Dependency Treebank

Nov. 27-28, 2006

The Prague Dependency Treebank – “the Data”



- (1) The Prague Dependency Treebank (PDT)
 - Introduction, token level, morphology
 - “Physical” markup / intro
- (2) The Syntactic Annotation of the PDT
 - Surface syntactic annotation
 - “Deep” Syntactic Structure, Valency (intro)
 - [(3) Topic/focus, Coreference, Grammatemes]
 - (4) Tectogrammatical Annotation & Valency Lexicon
 - Verbs and Nouns: Relating Form, Syntax and Semantics
 - Linking the Corpus and the Lexicon
 - Using the annotated corpus – further research and tools

2

VnIC Tutorial: The Prague Dependency Treebank

Nov. 27-28, 2006



The Prague Dependency Treebank Project (Czech Treebank)

- 1996-2005-...
 - 1998 PDT v. 0.5 released (JHU workshop)
 - 400k words annotated, unchecked
 - 2001 PDT 1.0 released (LDC):
 - 1.3MW annotated, morphology & surface syntax
 - 2005 PDT 2.0 release planned
 - 0.8MW annotated (50k sentences)
 - the “tectogrammatical layer”
 - underlying (deep) syntax

VnIC Tutorial: The Prague Dependency Treebank

4



Prague Dependency Treebank Intro, tokens, morphology (p. 1)

- Introduction to the Prague Dependency Treebank family of projects
- Text base, tokenization, sentence boundaries
- Morphology
 - Lexicon, lemmatization
 - Inflection morphology
 - Tagset
 - Manual annotation process

Nov. 27-28, 2006

3

VnIC Tutorial: The Prague Dependency Treebank

Related Projects (Treebanks)

- Prague Czech-English Dependency Treebank
 - WSJ portion of PTB, translated to Czech
 - automatically analyzed
 - English side (PTB), too
- Prague Arabic Dependency Treebank
 - apply same representation to annotation of Arabic surface syntax so far
 - Both have been published in 2004 (LDC)
 - Czech Academic Corpus v. 1.0 (2006)
 - Conversion of 70s' style annotation to PDT style (0.5 mil.)

Nov. 27-28, 2006

VMC Tutorial: The Prague Dependency Treebank

5

PDT (Czech) Data

- 4 sources:
 - Lidové noviny (daily newspaper, incl. extra sections)
 - DNES (Mladá fronta Dnes) (daily newspaper)
 - Vesmír (popular science magazine, monthly)
 - Českomoravský Profit (economical journal, weekly)
- Full articles selected
 - article ~ DOCUMENT (basic corpus unit)
- Time period: 1990-1995
- 1.8 million tokens (~110 thousand sentences)

6

VMC Tutorial: The Prague Dependency Treebank

PDT Annotation Layers

- L0 (w) Words (tokens)
- automatic segmentation and markup only
- L1 (m) Morphology
 - Tag (full morphology, 13 categories), lemma
- L2 (a) Analytical layer (surface syntax)
 - Dependency, analytical dependency function
- L3 (t) Tectogrammatical layer (“deep” syntax)
 - Dependency, functor (detailed), grammemes, ellipsis solution, coreference, topic/focus (deep word order), valency lexicon

Nov. 27-28, 2006

VMC Tutorial: The Prague Dependency Treebank

7

Tokenization, Segmentation, Sentence Breaks (L0, w-layer)

- Basic Principles
 - Fully automatic
 - Will have to be the same for the manually annotated part as well as for other plain-text data
- No access to any linguistic knowledge
 - ...beyond, say, really fail-safe lists of certain types of abbreviations, language identification, coding scheme, and letter classification (upper/lower/...)
- Standard output markup
 - unified coding scheme (today, Unicode in most cases)

VMC Tutorial: The Prague Dependency Treebank

8

Tokenization

- Words
 - What is a word? (word boundaries)
 - Treatment of hyphens, apostrophes, periods, ...
 - Numbers w/digits (normalization)
 - “periods”, thousand separators
 - Types of numbers (?)
 - cardinal, ordinal, money, SSN, tel/fax/..., dates, ...
 - Mixed letters and digits
 - Rule of thumb:
 - Split whenever there is the slightest doubt!

Nov. 27-28, 2006

VMC Tutorial: The Prague Dependency Treebank

9

Tokenization

- Words
- Capitalization
 - Main issues (the “true case”):
 - Names (not identified yet!)
 - Start of sentence (don’t know it yet either!)
 - Typographical conventions (unmarked in most cases)
 - Nontrivial
 - Headings
 - Rule of thumb:
 - don’t solve it (yet), just keep it & possibly mark it

10

VMC Tutorial: The Prague Dependency Treebank

(No) Segmentation, I

- Segmentation ~ (for us) splitting “inside” words (“between two letters”)
 - examples (not segmented in PDT):
 - elektro|technický (*electrotechnical*)
 - bílo|červeno|modrý (*white-red-blue*)
 - tisícilhávý (*one-thousand-headed*)
 - polohšílený (*half-mad*)
 - naič = na co (onto what, contraction (~ ‘isn’t’))
 - pracovalls = pracoval jsi (you have worked, ~ ‘y’know’)
 - za|číš = za co jsi (for what you have <verb>)

Nov. 27-28, 2006

VMC Tutorial: The Prague Dependency Treebank

11

(No) Segmentation, II

- Ambiguity
 - přenos:
 - přenos
 - přenos
 - a few others
- However: it is not very frequent (Cz, En, Ar) →
 - can be handled by expanded dictionary & tagset design
 - therefore no segmentation (of this kind)!

12

VMC Tutorial: The Prague Dependency Treebank

Sentence Boundaries

- Chicken and egg problem:
 - To analyze a text linguistically, we need to know sentence boundaries...
 - but...
 - To know sentence boundaries, we would need to have the text linguistically analyzed.
- Solution:
 - Do something good enough in most cases
 - ...maybe redo it later in the manually annotated part

Nov. 27-28, 2006

VMC Tutorial: The Prague Dependency Treebank

13

PDT Annotation Layers

- L0 (w) Words (tokens)
 - automatic segmentation and markup only
- L1 (m) Morphology
 - Tag (full morphology, 13 categories), lemma
- L2 (a) Analytical layer (surface syntax)
 - Dependency, analytical dependency function
- L3 (t) Tectogrammatical layer ("deep" syntax)
 - Dependency, functor (detailed), grammatical categories, ellipsis solution, coreference, topic/focus (deep word order), valency lexicon

14

VMC Tutorial: The Prague Dependency Treebank



Morphological Attributes

- Prerequisites for the manual annotation process:
 - Tokenized data
 - Annotation guidelines
 - Annotation tool
 - Manual decision making support
 - Offline (or online) morphological analyzer
 - Quality checking tool
 - Process description
 - Results (manually annotated data) to be used for...
 - tagger training, linguistic research, basis for further annotation, ...

Nov. 27-28, 2006

VMC Tutorial: The Prague Dependency Treebank

15



Morphological Attributes

- Ex.: nejnezajímaříš m
"to_i the most uninteresting"
- Tag: 13 categories
 - Example: **A****AFF****P3** - **-3N**
- negated
- no voice
- no poss. Number
- no poss. Person
- no tense
- superlative
- base var.


- Lemma: POS-unique identifier
- Books/verb -> **book-1**, went -> **go**, to/prep. -> **to-1**

16

VMC Tutorial: The Prague Dependency Treebank

The Process of Morphological Annotation

- From tokenized to annotated text:



Nov. 27-28, 2006 VMC Tutorial: The Prague Dependency Treebank

21

The Segmentation Problem: Possible solution (Arabic)

- Tokenization / segmentation not always trivial
 - Arabic, German, Chinese, Japanese
- Find max. no. of segments
 - 4 for Arabic
- expand every solution (morph. analysis) to the same number of segments, adding "blank" segments to the end
- concatenate tags (\rightarrow same length)
- concatenate "lemmas" (roots, ...)
- Result:
 - the same formal definition; can be converted back to segments trivially
 - tagging solves segmentation!

Nov. 27-28, 2006 VMC Tutorial: The Prague Dependency Treebank

23

Using the Results: Morphological Disambiguation

- Full morphological disambiguation
 - more complex than (e.g. English) POS tagging
- Three taggers:
 - (Pure) HMM
 - Feature-based (MaxEnt-like)
 - used in the PDT distribution
 - Voted Perceptron, (M. Collins, EMNLP'02)
 - All: ~ 94-5% accuracy (perceptron is best)
 - rule & statistic combination: tiny improvement (Hajic et al., ACL 2001)

Nov. 27-28, 2006 VMC Tutorial: The Prague Dependency Treebank

22

For your notes...



Nov. 27-28, 2006 VMC Tutorial: The Prague Dependency Treebank

24

Part 2

**DATA (continued):
The Prague Dependency
Treebank**

The Prague Dependency Treebank and Valency Annotation (part 2)

Jan Hajic
Institute of Formal and Applied Linguistics
School of Computer Science
Faculty of Mathematics and Physics
Charles University, Prague
Czech Republic

PDT – Syntactic Annotation (tutorial part 2)

- Surface syntax annotation
 - Dependency surface syntax
 - Comparable to Penn Treebank annotation
 - Convertible: dependency \leftrightarrow parse trees
- Deep syntactic/semantic annotation
 - Dependency trees
 - Different topology
 - High level of generalization and formalization
 - Many node attributes

2




PDT Annotation Layers

- L0 (w) Words (tokens)
 - automatic segmentation and markup only
- L1 (m) Morphology
 - Tag (full morphology, 13 categories), lemma
- L2 (a) Analytical layer (surface syntax)
 - Dependency, analytical dependency function
- L3 (t) Tectogrammatical layer (“deep” syntax)
 - Dependency, functor (detailed), grammemes, ellipsis solution, coreference, topic/focus (deep word order), valency lexicon



Layer 2 (a-layer): Analytical Syntax

- Dependency + Analytical Function



The influence of the Mexican crisis on Central and Eastern Europe has apparently been underestimated.

4


Analytical Syntax: Functions

- Main (for [main] semantic lexemes):
 - Pred, Sb, Obj, Adv, Atr, Atv(V), AuxV, AuxG, Phom
 - “Double” dependency: AttrAdv, AttrObj, AttrAtr
- Special (function words, punctuation,...):
 - Reflexives, particles: AuxT, AuxR, AuxO, AuxZ, AuxY
 - Prepositions/Conjunctions: AuxP, AuxC
 - Punctuation, Graphics: AuxX, AuxS, AuxG, AuxK
- Structural
 - Ellipsis: ExD, Coordination etc.: Coord, Apos

5

Surface Syntax Example


- Complete sentence: Sb, Pred, Obj
 - The-baker bakes rolls.
 - Pekař peče housky.



7

Example


- *lit. That it will go wrong, (that) was clear immediately.*
 - Že bude zle, bylo jasné hned.



6

Surface Syntax Example

- Analytical verb form:
 - (he) allowed would-be-to-be enrolled
 - směl by byt zapsán




8

Surface Syntax Example

- Predicate with copula (state)

- (the) pool has-been already filled
- bazén byl již napuštěn




9

Surface Syntax Example

- Passive construction (action)

- (The) book has-been translated [by Mr. X]
- Kniha byla přeložena




10

Surface Syntax Example

- Complement

- we (are) came three
- my jsme přišli tři




11



Surface Syntax Example

- Complement when NP is missing


- (he) has cooked [his meals]
- má uvařeno



12

Surface Syntax Example


- Object
 - (he) gave him a-book
 - dal mu knihu



13

Surface Syntax Example

- Object used for infinitive of analytical verb forms
 - (he) Could come
 - Mohl by přijít




14

Surface Syntax Example

- Relative clause (embedded)


- (a) house, which is expensive, (we) (to-ourselves) will-not-buy nekoupíme
- dům , který je drahý , si



15

Surface Syntax Example

- Coordination
 - ... (to) magic, mystic(,) etc.
 - ... magii , mystice apod.




16

Surface Syntax Example

- Apposition

- cheap, i.e. under 5 crown
- levný , tj. pod 5 korun




17

Surface Syntax Example

- Incomplete phrases

- Peter works well , but Paul badly
- Petr pracuje dobré, ale Pavel špatně




18

Surface Syntax Example

- Variants (equality)

- (he) bought shoes for boy
- koupil boty pro kluka



19

Using the Results: Parsing

- Several parsers of Czech


- Analytical layer dependency syntax
- Trained on PDT 1.0 dat, 1.2 mil. words
- Collins (98), Charniak (00), Žabokrtský (02), Ribarov (04), Nivre (05), Zeman(05), McDonald (05)

- Best results (accuracy: percent of correct dependencies):
- 84-85% for a single parser, > 86% for a combination

20

The Prague Markup Language (Intro only – see P. Pajas, p. 6)

- XML-based, UTF-8 coding used
 - Stand-off annotation
 - strict hierarchical scheme
 - 4 files for each annotated document ~ 4 layers of annotation
 - Can capture intermediate annotation
 - e.g., ambiguous analysis after morphological preprocessing
 - Lexical resources linked in
 - valency lexicon referenced from t-layer data



- Strictly top-down links
 - w+m+a can be easily “knitted”
 - API for cross-layer access
 - (programming)
 - PML Schema / Relax NG
 - [With slight modification, can be used for spoken data (audio as layer “1”)]

21

The Prague Markup Language Example

- m-layer data, linked to w-layer:

```
<m id="m-tr/_12941_01_00013.fs-s1w4">
  <src.rf>manual</src.rf>
  <w>
    <dest.r><w#v-tr/_12941_01_00013.f
      <trans>basic</trans>
    </w>
  <form>pocházela</form>
  <lemma>pocházel</lemma>
  <tag>vpQW---XR-AA---</tag>
</m>
<m id="m-tr/_12941_01_00013.fs-s1w5">
```

Pointer to w->a

PDT Annotation Layers

- L0 (w) Words (*tokens*)
 - automatic segmentation and markup only
 - L1 (m) Morphology
 - Tag (full morphology, 13 categories), lemma
 - L2 (a) Analytical layer (*surface syntax*)
 - Dependency, analytical dependency function
 - L3 (t) Tectogrammatical layer (“deep” *syntax*)
 - Dependency, functor (*detailed*), grammatical, ellipsis solution, coreference, topic/focus (*deep word order*), valency lexicon

22

Layer 3 (t-layer): Tectogrammatical Annotation


- Underlying (deep) syntax
 - 4 sublayers (integrated):
 - dependency structure, (detailed) functors
 - valency annotation
 - topic/focus and deep word order
 - coreference (mostly grammatical only)
 - all the rest (grammatemes):
 - detailed functors
 - underlying gender, number, ...
 - Total
 - 39 attributes (vs. 5 at m-layer 2 at a-layer)

33 Επιχειρηματίες (8): 3 ΑΙ ΣΤΙΓΜΑΥΕΙΣ, Ζ ΑΙ ΑΙΓΑΙΟΙ

25

Analytical vs. Tectogrammatical annotation (TR: sublayer 1 only)

annotation (τ_R : sublayer 1 only)



26

Layer 3: Tectogrammatical


- Underlying (deep) syntax
 - 4 sublayers:
 - dependency structure, (detailed) functors
 - topic/focus and deep word order
 - coreference (mostly grammatical only)
 - all the rest (grammatemes):
 - detailed functors
 - underlying gender, number, ...

27

Example - TR

- Graphical visualization
 - He worked as an engineer and he liked the work.

28



28


Dependency Structure

- Similar to the surface (Analytical) layer...
...but:
 - certain nodes deleted
 - auxiliaries, non-autosemantic words, punctuation
 - some nodes added
 - based on word (mostly verb, noun) valency
 - some ellipsis resolution
 - detailed dependency relation labels (functors)

29

Tectogrammatical Example

- Analytical verb form:
 - (he) allowed would-be to-be enrolled
 - směř byt zapsán



31

Tectogrammatical Functors

- “Actants”: syntactic, semantic
 - “Actants”: ACT, PAT, EFF, ADDR, ORIG
 - modify: verbs, nouns, adjectives
 - cannot repeat in a clause, usually obligatory
 - Free modifications (~ 50), semantically defined
 - can repeat; optional, sometimes obligatory
 - Ex.: LOC, DIR1, ..., TWHEN, TTILL, ..., RSTR; BEN, ATT, ACMP, INTT, MANN; MAT, APP; ID, DPHR, ...
 - Special
 - Coordination, Rhematizers, Foreign phrases,...

30

Tectogrammatical Example


- Predicate with copula (state)
 - (the) pool has-been already filled
 - bazén byl již napuštěny



32

Tectogrammatical Example

- Passive construction (action)
 - (The) book has-been translated [by Mr. X]
 - Kniha byla přeložena




33

Tectogrammatical Example

- Object

- (he) gave him a-book
 - dal mu knihu




34

Tectogrammatical Example

- Relative clause (embedded)

- (a) house, which is expensive, (we) (to-ourselves) will-not-buy nekoupíme
 - dům , který je drahý , si




35

Tectogrammatical Example

- Incomplete phrases

- Peter works well , but Paul badly
 - Petr pracuje dobré, ale Pavel špatně



36

Layer 3: Tectogrammatical

- Underlying (deep) syntax
- 4 sublayers:
 - dependency structure, (detailed) functors
 - topic/focus and deep word order
 - coreference (mostly grammatical only)
 - all the rest (grammatemes):
 - detailed functors
 - underlying gender, number, ...

37


Deep Word Order Topic/Focus

- Deep word order:
 - from “old” information to the “new” one (left-to-right) at every level (head included)
 - projectivity by definition (almost...)
 - i.e., partial level-based order -> total d.w.o.
- Topic/focus/contrastive topic
 - attribute of every node (t, f, c)
 - restricted by d.w.o. and other constraints

39

Deep Word Order, Topic/Focus (intro only: see E. Hajíčová, p.3)

- Example:



- Baker bakes rolls. vs. Baker^C bakes rolls.



38



Layer 3: Tectogrammatical


- Underlying (deep) syntax
- 4 sublayers:
 - dependency structure, (detailed) functors
 - topic/focus and deep word order
 - coreference (mostly grammatical only)
 - all the rest (grammatemes):
 - detailed functors
 - underlying gender, number, ...



40

Coreference (intro only: see E. Hajíčová p.3)


- Grammatical (easy)
- relative clauses
 - which, who
 - Peter and Paul, who ...
- control
 - infinitival constructions
 - John promised to go ...
 - reflexive pronouns
 - {him, her, thme}self(-ves)
 - Mary saw herself in ...



41

Coreference

- Textual
 - Ex.: Peter moved to Iowa after he finished his PhD.




42



Grammatemes (intro only: see Z. Žabokrtský p. 3)

- Detailed functors (subfunctors)
 - only for some functors:
 - TWHEN: before/after
 - LOC: next-to, behind, in-front-of, ...
 - also: ACMP, BEN, CPR, DIR1, DIR2, DIR3, EXT
- Lexical (underlying)
 - number (SG/PL), tense, modality, degree of comparison, ...
 - strictly only where necessary (agreement!)



Layer 3: Tectogrammatical

- Underlying (deep) syntax
- 4 sublayers:
 - dependency structure, (detailed) functors
 - topic/focus and deep word order
 - coreference (mostly grammatical only)
 - all the rest (grammatemes):
 - detailed functors
 - underlying gender, number, ...


43



44




Fully Annotated Sentence



46



Example - simplified view



45

Part 3

DATA (continued): The Prague Dependency Treebank

Grammatemes in the PDT 2.0

Zdeněk Žabokrtský
Dept. of Formal and Applied Linguistics
Charles University, Prague
zabokrtsky@ufal.mff.cuni.cz

1

What is not a grammame?

- grammatemes are not just straightforward counterparts of surface morphological categories (as stored in m-layer tags)!
- some morphological categories are only imposed by grammar and thus are not semantically relevant
 - gender, number or case of an adjective in a noun group come from agreement with the noun (e.g. in Czech or German), not from semantics
 - similarly, person is not a grammame of verbs, as it is only induced by subject-verb agreement
- on the surface, grammates can be expressed both inflectionally and analytically -> info about grammates can be distributed over more than one m-layer token
 - comparative of adjectives in English (*more interesting*)
 - future tense of imperfatives in Czech (*budu chodit... / I will go...*)

3

2

Complete list of grammame attributes used in PDT 2.0

- PDT 2.0
- gram/number - number of semantic nouns
 - gram/gender - gender of semantic nouns
 - gram/person - person of pronominal semantic nouns
 - gram/politeness - basic vs. polite/esteemed form, relevant for pronominal semantic nouns
 - gram/indeftype (type of indefiniteness of pro-forms)
 - gram/numertype (type of numeric expression)
 - gram/negation - negation of semantic nouns, adjectives, and adverbs (not of verbs)
 - gram/degcmp - degree of comparison of semantic adjectives and adverbs
 - gram/tense - tense of verbs
 - gram/aspect - aspect of verbs
 - gram/verbmod - basic verb modality (indicative, imperative, conditional)
 - gram/deontmod - deontic modality expressed by modal verbs
 - gram/dispmod - dispositional modality (specific for Czech)
 - gram/resultativ - resultativity of verbs
 - gram/iterativeness - iterativeness of verbs
 - grammod - sentence modality (enunciative, exclamative, desiderative, imperative, interrogative)

4

Grammateme number

PDT 2.0

- values:
 - sg - singular
 - pl - plural
 - nr - not recognized

m-layer/t-layer asymmetry:

- pluralia tantum: jedny dveře/ dvouje dveře (one door, two doors)
 - only the plural form exists at the m-layer, but sg/pl should be disambiguated at the t-layer
- polite form: "Viděj jste to, Petr?" (Did you see it, Petr?) – complex verb form containing an auxiliary verb in plural at the m-layer, but at the t-layer the grammateme number (filled in the reconstructed #PersPron node) is equal to singular

5



Grammateme tense

PDT 2.0

- values:
 - relative tense of verbs (with respect to the tense of the governing clause)
 - sim - simultaneous
 - ant - anterior
 - post - posterior
 - nil - absent (with infinitives)
 - nr - not recognized

m-layer means for expressing tense=past in Czech:

- inflection with perfectives (*uvářím* - I will cook)
- auxiliary verb *byť* with imperfectives (*budu zpívat* - I will sing)
- prefix *po-/př-* with a limited set of verbs (*pojedu* - I will go)

6



Grammateme indeftype (I)

PDT 2.0

- pro-form - a word used to replace or substitute other words, phrases, clauses...
- pronouns (pro-nouns), pro-adjectives, pro-numerals, pro-adverbs
- there are many semantically significant analogies present in the pro-forms systems, but usually not explicitly distinguished in the POS tag sets
- example of such parallelism:
 - nobody/never/nowhere... vs. everybody/always/everywhere...
- grammateme indeftype (type of indefiniteness) dedicated for all indefinite pro-forms
- to capture the parallelisms, each group of pro-forms is represented with t_lemma identical with the relative form: *někde->kde* (nowhere->where), *kdo/-kdo* (whoever->who), *nikdy->kdy* (never->when)

7



Grammateme indeftype (II)

PDT 2.0

t-lemma:	kdo	co	který	jaky
value of the grammateme indeftype:				
relat	kdo	co	kteří,jenž	jaky
indef1	někdo	nečo	některý	nějaký
indef2	kdoši, kdoš	cosi, cos	kteřysi	jaky/si
indef3	kdokoliv	cokoliv...	kteřikoliv	jakykoliv
indef4	ležákdo, lečkdo...	ledaco, lecc...	ležákterý, lečkterý	legáký, ledáký
indef5	kdeko	kdéco	kděkterý	kdějaký
indef6	málokdo, kdovíkdo...	máloco...	málokterý...	všelijaký...
inter	kdo, kdopak...	co, copak...	kteří, kteřipak	jaky, jakýpak
negat	nikdo	nic	žádný	nijaký
total1	všechn	všechn,	–	–
total2	–	–	každý	–

8



Grammatical indeftype (III)

PDT 2.0

- indefinite, negative, interrogative, and relative pronouns and other pro-forms are unproductive classes with (at least to a certain extent) transparent derivational relations also in other languages
- preliminary sketch of several English and German pronouns classified by indeftype

Lemmat	English	English	German	German
indeftype:		what	wer	was
relat	who	what	wer	was
indef1	someone	something	jemand	etwas
indef2	-	-	irgendjemand	irgend etwas
indef3	whoever	whatever	-	-
inter	who	what	wer	was
negat	nobody	nothing	niemand	nichts
total1	all	everything	alle	alles
total2	each	each	jeder	jedes

9



Typing of t-nodes

PDT 2.0

- unlike t_lemmas and functors, grammaticeme attributes are not relevant for all t-nodes
- obviously, no tense for dog, no degree of comparison for (he) waits, etc.
- crucial question: how to formally declare presence/absence of a certain grammaticeme in a certain t-node? → the need for node typing



- our solution: two-level hierarchy of node types
 - 1st level: 8 coarse-grained types of nodes
 - 2nd level: 19 more specific subtypes, corresponding to detailed semantic parts of speech

10



Two-level hierarchy of t-node types

PDT 2.0



First level of the hierarchy: attribute nodetype

PDT 2.0

- 8 node type values:

- root | complex | qcomplex | list | atom | coap | dphr | fphr
- fully automatic annotation - use of
 - the tree structure → root
 - t-attributes
- t-lemma → qcomplex | list
- functor → atom | coap | dphr | fphr
- otherwise → complex


11

Levnější benzín na Východě, dražší na Západě
Cheaper gasoline in the East, more expensive one in the West

PDT 2.0

Second level of the hierarchy: attribute sempos


- sempos relevant only for nodetype=complex t-nodes
- 19 values of the attribute sempos:
- fully automatic annotation - use of



13

PDT 2.0


M-layer POS tags vs. sempos



14

PDT 2.0

Pro-forms: m-layer tags vs. t-layer sempos



15

PDT 2.0

Grammateemes: Annotation process

- implementation: 2000 Perl LOCs in the ntred environment
- 2000 lines of linguistic rules in a special notation
- extensive usage of m-layer and a-layer manual annotation -> mostly automatic annotation possible
- only 5 man-months of human annotation

16



More reading about grammaticalemes

- Chapter 2.4 in the t-layer manual (included in the PDT 2.0 documentation)
- Razímová, M., Žabokrtský, Z.: *Morphological Meanings in the Prague Dependency Treebank 2.0*. In: Proceedings of TSD. 2005
- Razímová, M., Žabokrtský, Z.: *Annotation of Grammaticemes in the Prague Dependency Treebank 2.0*. Proceedings of Annotation Science Workshop, LREC. 2006
- Ševčíková Razímová, M., Žabokrtský, Z.: *Systematic Parametrized Description of Pro-forms in the Prague Dependency Treebank 2.0*. In: Proceedings of TLT. 2006

17

Annotation

of the Topic-Focus Articulation in the Prague Dependency Treebank

Eva Hajíčová

1

Overview

1. Linguistic motivation of TFA annotation:
 - i. Basic notions
 - ii. Why TFA should be annotated in the TGTS's: semantic relevance of TFA
2. TGTS attribute TFA and its values
3. Examples
4. Testing linguistic hypotheses on a deep layer of corpus annotation

Basic notions of TFA

- Information structure of the sentence
 - Topic-focus articulation
 - Topic, theme, ...
 - Focus, rheme, ...
 - based on *given* x *new*, but not identical to this cognitive dichotomy:
 - John and Mary entered the dining-room. They first went to the window ...
 - Mary Called Jim a Republican. Then he insulted HER.
 - Mary called Jim a republican. Then he INSULTED her.

2


3

Semantic relevance of TFA

- Everybody in this room knows two languages.
Two languages are known by everybody in this room.
- Many men read few books.
Few books are read by many men
- Smoke in the hallway!
In the hallway, you smoke.
- Staff behind the COUNTER.
STAFF behind the counter.
- Carry DOGS.
CARRY dogs. Dogs must be carried.

4

Example *Na světě nejsou jenom brouci. [In the-world there-are-not only beetles.]*




Topic-focus articulation in PDT

- one attribute (TFA – topic-focus articulation)
with values concerning the *contextual boundness* of the nodes
- three values in the TFA attribute:
 - t – contextually bound non-contrastive
 - c – contextually bound contrastive
 - f – contextually non-bound

5


Example *Zájem zvýšila i promyšlená reklama. [The-interest_Acc raised also the-sophisticated campaign.]*




6

7

Example Nenadálon finanční krizi podnikatelka řešila jiným způsobem. [The sudden financial crisis _Acc the-entrepreneur_Nom solved by other means.]



Example Jen dobré srdce bezmocným nepomůže. [Only good heart the-helpless_Dat will-not-help.]



- Corpus annotation is not a self-contained task.
- A necessary condition for a usable annotated corpus: based on a sound linguistic theory.
- PDT: linguistic basis: Functional Generative Description.
- One of the important uses of corpus: test for linguistic theories.

Testing linguistic hypotheses

Hypothesis A1:

- the global division of the sentence into its TOPIC (what the sentence is about) and its FOCUS (what is said about the topic) can be made on the basis of boundness

Sgall (1979; see also Sgall et al. 1986 216f), original algorithm implemented and tested on the whole of PDT; the results reported in Hajičová, Havelka and Veselá (2005)

Hypothesis A1: Division into T and F based on boundness

Hypothesis A1:

- the global division of the sentence into its TOPIC (what the sentence is about) and its FOCUS (what is said about the topic) can be made on the basis of boundness

Sgall (1979; see also Sgall et al. 1986 216f), original algorithm implemented and tested on the whole of PDT; the results reported in Hajičová, Havelka and Veselá (2005)

Hypothesis A1 (cont.)


- a) main verb = f → belongs Focus (F); else, → T
- b) all the nodes directly dependent on the main verb and carrying t → T, together with all nodes depending on them
- c) all the nodes directly dependent on the main verb and carrying f → F, together with all nodes depending on them
- d) main verb = t & all nodes directly depending on the main verb = t: follow the rightmost edge leading from the main verb to the first node(s) on this path carrying the value f → this/these node(s) and all the nodes depending on it/them = F

12

Example *Firma dnes působí ve čtyřech zemích světa.* [The-firm now operates in four countries of-the-world.]

t-cmp9413-049-p6s2

root



13

Results of the implementation

- F: V + subtrees
- F: right-attached subtrees of V.t
- Quasi-focus
- F interrupted by c-node
- Ambiguous partition
- No focus identified

85,7%

8,58%

4,41%

0,06%


1,14%

0,11%

Example *Času přiliš nezbývá. [Time_Gen too-much* *does-not-remain.]*

t-ln94209-18-p3s3

root



přiliš
adv.denot.ngrad.neg

Results

- in Czech: the boundary between Topic and Focus can be determined in principle on the basis of the consideration of the **status of the main predicate** and its direct dependents.
 - TFA annotation leads to satisfactory results in cases of rather complicated “real” sentences in the corpus.
- Certain modification of the annotation procedure necessary, but the material gathered and analyzed in this way may be further used for the study of several aspects of the **discourse patterning**.

16

Hypothesis A2: The so-called systemic ordering

Hypothesis A2:

- In the focus part of the sentence the complementations of the verb (be they arguments or adjuncts) follow a certain canonical order (not necessarily the same for all languages).

17

tested with a series of psycholinguistic experiments (with speakers of Czech, German and English) but PDT offers a richer and more consistent material → work in progress (Lešnerová)


Hypothesis A2: (cont.)

Tested on PDT

- the F of the sentence identified (see A1)
- in TGTS: the surface order in F preserved
- systemic ordering hypothetically stated

→ these pieces of information used to compare the order of the complementations in the actual sentence and the assumed order according to the scale of systemic ordering


Example Londýn se stáhl za La Manche. [London Refl. Withdrew back behind La Manche.]



18

19

Example Barokní gala koncert se uskuteční zítra v Rudolfinu. [A-baroque gala concert Refl. Will- take-place tomorrow at Rudolfinum.]



20

21

Conclusions

- importance of the deep-layer corpus annotation for the **study** of most various language phenomena
- the tectogrammatical layer of annotation brings about an indispensable source of information for **testing** any linguistic **theory** and any **grammar build-up**

Coreferential Relations in the Prague Dependency Treebank

Eva Hajčová

PDT layers and coreference

- The three PDT layers – capture grammatical information
- Coreference relations – textual relations – “beyond” grammar

BUT:

the aim: by annotating these relations to get more insight into the inter- and intrasentential structure

1

2

Tectogrammatical annotation

- semiautomatic → user-friendly tree editor (TRED)
 - 3 steps (phases):
 - build-up of underlying syntactic tree structures (incl. nodes deleted on the shallow structure) and assigning the nodes functional labels
 - adding the values of the topic-focus attribute
 - adding the coreferential links

3

Annotation of coreference relations in PDT

- coreference relations in the narrower sense
 - a binary relation between an anaphor and an antecedent:
 - the antecedent may be in a different TGTS
 - the antecedent may also be an entity that is not represented in any TGTS
 - 2 kinds of coreference
 - grammatical
 - textual

4

Annotational scheme

- explicit coreference links are technically represented as pointers (pml reference) leading from anaphor t-nodes to their antecedent t-nodes
- three coreferential attributes with an anaphor:
 - **coref_gram.rf** – identifier (or a list of identifiers) of the antecedent(s) in the sense of grammatical coreference
 - **coref_text.rf** – identifier (or a list of identifiers) of the antecedent(s) in the sense of textual coreference
 - **coref_special** – special types of coreference:
 - 1. **segm** – coreference with a sequence of preceding sentences (further underspecified)
 - 2. **exoph** – antecedent not present in the text at all

5

Notational devices for coreferential links in PDT

- arrows from the anaphor to the antecedent(s)
- different colours of the arrows according to the type of coreference
 - special devices: an exophora, a segment
 - an annotator-friendly special module within the TRED editor

6

Grammatical coreference

- verbs (nouns, adjectives) of control
 - John asked Mary to [θ] come.*
 - reflexive pronouns
 - John shaved himself.*
 - relative pronouns
 - John, who came late, apologized.*
 - verbal complements
 - John came [θ] bare-footed.*
 - reciprocity
 - John and Mary kissed [θ].*

Lit.: (*When*) time-ago he paid in-London with-50-pound banknote expenditure of-8 pounds, checked it several clerks (*before*) they took it from-him.

Textual coreference

- Present stage:
 - in the whole PDT 2.0
 - demonstrative and anaphoric pronouns
(also in their zero form), 3rd person
 - bridging anaphora is not included
 - in a sample of 80 PDT documents
 - anaphoric relations leading from nouns
 - incl. a rough classification of bridging anaphora

Types of textual coreference

- link to a particular node
 - link to the governing node of a subtree
 - **segm(ent)**: referent is a whole segment of text
 - **exoph(or)**: referent is „out“ of co-text
 - **unsp(ecified)**: reference is difficult to be specified

Link to a particular node

- this node represents an antecedent of the anaphor:

Do you think that the decision of NATO whether [it] will be enlarged or not will depend on the attitude of Russia?

→ the link from **it** leads to **NATO**

11

Link to the governing node of a subtree

- antecedent is represented by this node plus (some of) its dependents; also the way how a link to a previous/following clause or a whole previous sentence is being established:

But it is a different thing when someone is an entrepreneur and then goes into politics than when political changes elevate somebody to the top and he then uses this in his economic activities.

→ the link from **this** points to the root of the tree (*elevate*) = to the main verb of the second conjunct.

12

Segm(ent)

- referent is a whole segment of (previous) text larger than one sentence (phrase):

According to Kohl it should not be forgotten that on June 22, 1941 Germany attacked the Soviet Union. Germans on behalf of Germany caused the Russians to suffer immensely. It also cannot be forgotten what the Russians did to Germans. From all this we should learn.

13

Segm(ent) 2

- includes also the cases, when the antecedent is understood by inferencing from a broader co-text:

The big shots buy in a bank for ten and sell for fifteen. But this leads to a rapid transformation. The acrages of about 25 ha disappear, the number of owners raises to 500. I guess that within two years they will be able to pay back the debt to the bank and in the third year they will work for themselves. And they will hire only capable people, it will be in their best interest. Those who understand this, will have an advantage.

14

Exoph(or)

- a specifically marked link denoting that the referent is “out” of the co-text, it is known only from the situation:

*In the height of summer 1939 only a few people could believe the hopeful words Chamberlain uttered [...] after the return from Munich: I think that **this** is peace for our time.*

→ **this** = Munich Treaty

15

Unsp(ecified)

- a specific mark reserved for cases of reference difficult to be identified; a decision is not to be made between two or more referents but that the reference cannot be specified even if the situation is taken into account:

The disappearance of the medical instrument weighing 700 kg [they] announced on June 30th this year. According to the information of LN, however, the radiator disappeared by the end of the last year.

16

Statistics: volume of data

number of annotated documents (i.e. the whole PDT 2.0 t-layer data)	3 165
number of sentences/t-trees	49 431
number of t-nodes	724 396
total number of co-refering t-nodes	46 242 (6.3% of all)

17

Statistics: types of coreference

grammatical coreference	23 252 (50.3%)
textual coreference	22 368 (48.4%)
special types	
segm	505 (1.1%)
exoph	120 (0.2%)

18

Statistics: t-lemmas with anaphors (1)

most frequent t-lemmas with grammatical coreference	
1. který	7 435 (32% of all grammatical)
2. #Cor	5 907 (25%)
3. #PersPron	4 419 (19%)
4. #QCor	2 472 (10%)
5. #Rep	1 114 (4.7%)
6. co	575 (2.5%)
7. kde	555 (2.3%)
...	

19

Statistics: t-lemmas with anaphors (2)

most frequent t-lemmas with textual coreference	
1. #PersPron	18 622 (83%)
2. ten	3 733 (16.7%)
...	

20

Statistics: expressed vs. restored grammatical coreference

anaphors expressed in the surface shape	13 783 (59.3%)
restore anaphor nodes	9 469 (40.7%)
textual coreference	
anaphors expressed in the surface shape	11 131 (49.7%)
restored anaphor nodes	11 237 (50.3%)

21

Steps beyond: segm(ent)

The boundaries of the (relevant) segment are not quite clear:

The only reason for me to stay in America is money. [...] In America, I rent a house every year and at the end of the season I rush home. I have friends here, we go fishing, we play tennis, we visit each other. I often visit my parents in Martin. I am simply at home here. [...] In Canada this is totally different.

22

Steps beyond: exoph(ora)

Border-line between exophora and other types of coreferential relations:

→ coreference to an unspecified element:

A well-known native of Pardubice, Roman M. [...] had drunk himself to death after he found out that he was born in Hradec Králové. [...] The birth of children from Pardubice in Hradec Králové periodically happens. Once in every two years [they] brought them here, said the nurse at the obstetric clinic of the Hradec hospital.

→ coreference to a segment („inferential“ type):

Sad people write bright merry books and merry people write sad [ones]. One has to balance it somehow.

23

24

Pronoun with other than referential function

- Intensifying function – particle *to* (*ten*):
 - *Boy, is it raining! Lit. If that] but it-rains! = meaning: it rains very much.*
- Conceptually „empty“ occurrences:
 - *As I have imagined for a long time her trip abroad, to Spain or Greece, where [lit.] it draws her.*
- Phrasemes

○ *Lit. That you-have hard, this young person's father has connections.*

Open questions (1)

Coreferential link leads to the root

✗ antecedent is a part of sentence:

When Jiří Krupička sent me the manuscript of his Renaissance of Reason, which has been published now in the publishing house Český spisovatel, and I looked into it for the first time, not only my knees but also my heart trembled. And this [happened] for several reasons.

25

Open questions (2)

With a coreferential chain, all links are established:

The agreement of course has not solved anything – it only deepened the feeling in the protestants that London leaves them in the lurch. Today this feeling, that [they] are only a burden for Great Britain, which [they] do not know how to deal with, has strengthened in Ulster protestants.

26

Open questions (3)

- Nodes are reconstructed also with nominalizations:

It [=the word] has a strong emotive colouring and it occurs especially in discourse of young people.

colouring → Gen.ACT

→ Gen.PAT → *on.PAT* → *slovo* [word]

27

Work in progress (1)

- Nouns as anaphors: anaphoric relations leading from nouns

- Rough classification

- Identity

- Part and whole relation

- Function

- Other types (of bridging anaphora)

28

Work in progress (2)

- Discourse structure analysis:

Hypothesis: A finite mechanism exists that enables the addressee to identify the referents on the basis of a partial ordering of the elements in the stock of knowledge (information) shared by the speaker and the addressees (according to the speaker's assumption), based on the degrees of activation of referents.

Stock of shared knowledge

- SSH: a structured whole

- Hierarchy of activation of the SSK elements
 - a partial ordering

- Heuristic rules" for the assignment of degrees of activation based on:

- TFA value

- coreferential links

- outer form (pronoun, full noun group)

- Implementation of the rules and visualization of the results

29


30

Conclusions

- a systematic annotation of a large corpus of (segments of) continuous text(s) on several layers has an indisputable advantage
- there are, of course, many other respects in which corpus annotation schemes should go beyond the current practice
- there are no “frontiers” of the usefulness of annotated corpora both for linguistic theory and NLP applications

32

In95048_092_TF.dat



31

Part 4

DATA (continued): The Prague Dependency Treebank

The Prague Dependency Treebank and Valency Annotation (part 4)

Jan Hajíč
Institute of Formal and Applied Linguistics
School of Computer Science
Faculty of Mathematics and Physics
Charles University, Prague
Czech Republic


Prague Dependency Treebank Deep syntax & valency (part 4)

- Valency in the PDT
 - Valency lexicon for PDT
 - General valency lexicon
- Valency in deep vs. surface syntax
 - Links between the layers w.r.t. valency
- Valency and word sense
 - Sense-disambiguated occurrences:
 - Links from data to the lexicon
- Valency in translation, text generation


2

Definition of Valency

- Ability (“desire”) of words (verbs, nouns, adjectives) to combine themselves with other units of meaning
- Properties of valency:
 - Specific for every word meaning (in general)
 - leave: *sb left sth for sb* vs. *sb left from somewhere*
 - same as in PropBank *leave.02* vs. *leave.01*
 - Typically strongly correlates with surface form
 - morphological case (~ ending), preposition+case, ...
 - Semantic constraints ^{they are very dangerous}



Structure of Valency



3

4

The Valency Lexicon PDT-VALLEX

- Valency frames
 - each verb, some nouns, adjectives
- Basic set prepared in advance, annotators add entries on-the-go, checking and approval process follows (consistency)
- VALLEX
 - more detailed and complex annotation of valency
 - Žabokrtský, Lopatková (2005), VALLEX 1.0
 - All about valency:
<http://ufal.ms.mff.cuni.cz/~semecky/vallex/>

5

PDT-VALLEX Entry

- dosáhnout: “to reach”, “to get [sb to do sth]”
- browser/user-formatted example:

* dosáhnout
ACT(.1) PAT(2,4) v-w714f1 Used: 272x
dosáhnout určité jírovné
měla d. v tomto oboru srovnat
d. pokročilého větu
ACT(.1) PAT(2,aby[.v]) ?ORIG(na-1[.6],od-J[.2]) v-w714f2 Used: 7x
dosáhl na něm silbu
ACT(.1) DPHR(svij-j-1,2) v-w714f3 Used: 2x
dosáhl svého
ACT(.1) DIR3(*) v-w714f4 Used: 2x
dosáhl na zrop
rukou.MEANS

6



PDT-VALLEX Entry

- dosáhnout: “to reach”, “to get [sb to do sth]”
- browser/user-formatted example:

* dosáhnout
ACT(.1) PAT(2,4) v-w714f1 Used: 272x
dosáhnout určité jírovné
měla d. v tomto oboru srovnat
d. pokročilého větu
ACT(.1) PAT(2,aby[.v]) ?ORIG(na-1[.6],od-J[.2]) v-w714f2 Used: 7x
dosáhl na něm silbu
ACT(.1) DPHR(svij-j-1,2) v-w714f3 Used: 2x
dosáhl svého
ACT(.1) DIR3(*) v-w714f4 Used: 2x
dosáhl na zrop
rukou.MEANS

6



The Annotation Process

- 4 sublayers
 - work on structure first, rest in parallel
- Structure
 - automatic preprocessing - programmed conversion from analytical layer annotation
- Grammatemes
 - mostly automatically (based on lower layers' annotation), manual checking, corrections
- Cross-sublayer/cross-layer checking
 - partly automatic, then manual

7




Corpus <-> Valency Lexicon

- Corpus:
- Lexicon:
 - ex.: u. dohodu (close a contract)
 - ex.: u. pokoj (close a room, house)

8

The Annotation Scheme




9

Valency & Tectogrammatical Annotation

- Valency and...
 - (surface) form
 - Annotation tools
 - TrEd
 - structural annotation
 - valency lexicon integration
 - Search
 - TrEd, Netgraph


10

Valency & Form



lemma (AL): uvažovat
 ACT: surface ellipsis, node disappears
 PAT: preposition 'o' and a locative case

Tectogrammatical / Analytical



from another sentence: pravidlo.PL.PAT – pravidlo.PL.Acc(Obj)

11


12

Valency & Form

- Valency frame:
 - (per each sense of word)
 - (obligatory) modifiers \leftrightarrow functors
 - functor \rightarrow form
- Simplest case:
 - surface form of a functor: particular case
 - Ex.: ACT in nominative (he says)
 - Ex.: PAT in accusative (she sees him)
 - ... but it is not always so simple (as we have already seen)!

13

Valency & Form: Constraints

- Tree structure:
- (Sets of) Constraints:
 - n1: lemma=uvážovat mode=active
 - n2: case=Nom afun=S₀
 - n3: lemma=o afun=AuxP
 - n4: case=Loc afun=Obj

14

(General) Valency Lexicon Entries

Entry	Sense #	Frame #	Valency Optimality	Form alternatives
1	1	1	ACT PAT	$\nwarrow \{c_i\} \nearrow \{c_j\}$
2	2	2	ACT PAT LOC	$\nwarrow \{c_i\} \searrow \{c_j\}$
		3	ACT PAT DIR3	$\nwarrow \{c_i\}$
3	1	4	ACT PAT	$\nwarrow \{c_i\} \nearrow \{c_j\}$
2	2	2	ACT INTT	$\nwarrow \{c_i\} \nearrow \{c_j\}$
3	1	1	ACT PAT	$\nwarrow \{c_i\} \nearrow \{c_j\}$
	2	2	ACT PAT	$\nwarrow \{c_i\} \nearrow \{c_j\}$

15

Valency Lexicon Simplification

- Independent form for each slot of a particular valency frame
 - ACT, PAT, ...: own constraint, not a global one
- Functor_{oblig./opt.} \leftrightarrow constraints_{Functor}
- Ex.:
 - lemma1 ACT(Nom.) PAT(o+6) (to consider a rule)
 - lemma2 ACT(Nom.) PAT(4) (create a rule)
- Standard “transformations” of frame form
 - passivization, reflexivization, ...

16

Example: Valency & Form

- Simple 1:1:
 - ex.: create: ACT(Nom) PAT(Acc)
 - verb in infinitive: INTTT(Inf)
 - subordinate clause: PAT(verb)
 - class of words with generic verbs: CPHR({class})
 - no constraint: (often) LOC, TWHEN
 - general constraint for a given functor applies
 - ...more!

17

Example: Valency & Form

- 1:2
 - idomatic phrase



- linear representation: DPHR(interest.P4[own.#])

19


Example: Valency & Form

- 1:2
 - relative clause
- relative clause:
 - lemma=say mode=active
 - afun=AuxC lemma=that
 - to_say:
ACT
EFF
 - afun=Obj POS=verb
- linear representation: EFF(that[v])

18

Example: Valency & Form

- 1:3
 - idomatic phrase




- linear representation: EFF(that[v])

20

Example: Valency & Form

- 1:4
 - idomatic phrase




21

Valency and Translation

- leave:
 - leave-1
 - to leave [from] somewhere
 - leave-2
 - to leave sth for sb
 - Translating (from English into Czech):
 - which equivalent to choose?
 - nechat vs. odjet/opustit
 - which prepositions, cases, ... to use?
 - accusative vs. "z" ("from") with genitive vs. ...?

22

Valency and Translation




23

Valency and Text Generation

- Tectogrammatical Representation
 - has all the information to (re)generate the surface form of the sentence:
 - in a "generalized" form
 - non-redundant (almost.. but for generation, it is o.k.)
 - ...except the links to a-layer, however
 - links used only for training [statistical models for] parsing/generation modules
 - not present when e.g. doing text planning, translation, ...
- valency dictionary: form of "learned" knowledge

24

Valency and Text Generation

- Using valency for...
 - ...getting the correct (lemma, tag) of verb arguments
- Example:
VALLEX entry: starat (se) ACT(.1) PAT(o [4])



Tectogrammatical Annotation Tools

- Manual annotation
 - 4 groups of annotators ~ 4 sublayers
 - Special graphical tool (TrEd)
 - Customizable graphical tree editor
- Preprocessing
 - Data from analytical layer, preprocessed
 - Online dependency function preassignment

26



The “TrEd” Tree Editor

- Graphical tool
TrEd
- Main screen:


Original sentence:
[This year's flu season
is still quiet in Europe.]

Editing window
customization

Run a macro

Multiwindow
editing/compare

28




The [Manual] Annotation Tool

- Perl/PerlTk based, platform-independent
 - Linux, Windows 95/98/2000, Solaris, ...
- Perl as the “macro” language
 - “unlimited” online processing capability
- Flexibility for interactive checking
 - split screen, graphical “diff” function
- Customization, printing, “plugins”, ...
- !! See also J. Stepanek’s lecture / tools

27

Valency Lexicon in TrEd



29

The “Old” PDT 1.0

- Morphology (1.8MW) & Surface syntax (1.5MW)
- SGML format (csts.dtd) + compact “FS”
- Mixed (single-file) annotation
- 7 attributes + dependency
- TrEd (graphical viewer/editor), NetGraph (search capability)
- simple visualization

Annotating the Links

- Stand-off annotation principles
 - Links to another layer
 - Links to lexicon
 - Minimal work on link annotation (close to zero)
- Macro commands in TrEd
 - transparently keeps track of merged nodes, splits, etc., and adapts links correspondingly.
- Result:
 - almost no extra work
 - final check after annotators do the last pass

30

What’s New in PDT 2.0

- Tectogrammatical layer (0.8MW)
 - 39 node attributes + dependency
 - valency dictionary (PDT-VALLEX)
 - XML stand-off annotation (“PML”, 4 layers)
- New data division (train/dtest/etest)
 - added morphological annotation to all data
 - corrections of PDT 1.0 files (morphology, syntax)
- Improved tools:
 - TrEd, btrEd, ntred (batch tree corpus processing)
 - new features, better visualization




31

32

Tectogrammatical attributes |

- node typing
 - complex, coop, qcomplex, root, atom, ...
 - functor, subfunctor
 - TWHEN: TWHEN.basic, TWHEN.before
 - is_member, is_generated, is_parenthesis,
 - is_dsp_root, is_state, quot_type, ...
 - grammarmenes (16):
 - aspect, degcmp, deontmod, sempos, tense, indeftype, politeness, person, ...




PDT 2.0: The Data

- Data sizes

Tectogrammatical attributes ||

- topic/focus:
 - tfa, deepord
 - valency: t_lemma, val_frame.rf
 - bookkeeping: id
 - coref_gram.rf, coref_text.rf, compl.rf
 - reference to TR node, type of coreference
 - sentmod
 - Linking to analytical layer
 - a.lex.rf (“main” anal. node), a.aux.rf (others)



34

33

1

1

Using the Results (t-layer)

- Preliminary!
 - PDT 2.0 published July 2006
 - 50k sentences for training (t-layer)
- Functor assignment
 - > 80% accuracy on manually annotated structure
- Tectogrammatical parser
 - Part of the “toolchain” (run_all, see p. 5, p. 7, J. Štěpánek)
- Coreference
 - preliminary results: > 80%
- Valency
 - frame assignment > 70%

37

To take home...

- What is PDT
 - Dependency-based treebank project
 - Czech (other languages in the works)
 - ~ 1 mil. words
 - sufficient size for ML experiments
 - 4 layers of annotation
 - token, morphology, syntax, deep syntax/semantics++)
 - independent and full information at all levels, but...
 - interlinked (for the development of parsers/generators)
 - Valency dictionary integrated (links from data)

38

Some (more) pointers



- <http://ufal.mff.cuni.cz/pdt2.0>
 - Current version of PDT, all three levels, 1.9/1.5/0.8 Mw
- <http://ufal.mff.cuni.cz/REST/CAC/CAC.html>
 - The Czech Academic Corpus, v 1.0
- <http://www.ldc.upenn.edu>
 - LDC2001T10 (PDT v1.0), LDC2004T23 (PADT 1.0),
LDC2004T25 (PCEDT 1.0)
- [http://www.clsp.jhu.edu: Workshop 2002](http://www.clsp.jhu.edu:Workshop 2002)
 - Using TL for MT Generation

39

Part 5

TOOLS: **Annotation editors** **Browsers and viewers**

Lexical Annotation Workbench

LAW

Processing

- Input - morphologically annotated and lemmatized text (from automatic analysis)
 - several (many) possibilities for each token
- Manual selection of the right possibility
 - either from given options
 - or addition of a new option
- Output - morphologically annotated and lemmatized text - **desambiguated**
 - allowed more possibilities

Prague Treebanking for Everyone

Integrated environment
for morphological desambiguation
operating on m-layers

Filters

- only ambiguous
- only selected tags (regular expressions)
- only selected lemmas (regular expressions)
- only selected words (regular expressions)
- continuous filtering possible
- comparing two different m-layers

Annotation Editor for the Analytical and
Tectogrammatical Layer and Valency Lexicon

Jan Štěpánek

29th November 2006


Tree Editor TrEd

- Independent on operating system (MS Windows, Linux OS X...)
 - Open source program, available for free
 - Written in perl (macros, predefined functions)

Requirements and Installation

- perl (5.8.3 or newer) with Tk library
 - <http://ufal.mff.cuni.cz/~pajas/tred/>
 - For MS Windows: tred_winst_en.zip → setup.bat
 - For Linux: tred-dep-unix.tar.gz → install tred-current.tar.gz

TrEd Window




TrEd Window (2)

- 1 Main frame(s). Each frame displays one tree.
 - 2 A textual form of the sentence of the current tree.
 - 3 Status line – various information.
 - 4 Current context (set of macros). Can be changed by clicking and selecting a new one.
 - 5 Current stylesheet.
 - 6 “Edit stylesheet” button.
 - 7 Position of the current sentence in the file; “show sentences” button.
 - 8 Buttons to open, save and reload a file. The icons mean Undo, Redo, Previous and Next File, Print, Find, Find Next, Find Previous.
 - 9 Buttons for moving to the previous/next tree in the current file and for frame management.

Browsing Valency Lexicon

Browsing Valency Lexicon



Ctrl+Enter: ValLex entry for the current node

Browsing Valency Lexicon

Assigned valency frames(s)

Assigned valency frame(s) assigned to word item: devoat

Assigned valency frame(s) assigned to word item: vysvědčit.

Assigned valency frame(s) assigned to word item: záborň

Assigned valency frame(s) assigned to word item: pořádat


Assigned valency frame(s) assigned to word item: kam to ulížti.

Assigned valency frame(s) assigned to word item: výrode;

Assigned valency frame(s) assigned to word item: živat se

OK

Ctrl+V: Show the assigned valency frame



Ctrl+Shift+Enter: Browsing the ValLex

Corpus manager Manatee / Bonito

- Searching in corpora according to all attributes or their combinations (regular expressions)
 - Sorting and filtering results
 - Basic statistics
 - Graphical overview of occurrences within the whole corpus
 - Display of more attributes (word, lemma, different types of tags, ...)
 - Creating subcorpora

Searching

- most common attributes:
 - word
 - lemma
 - morphological tag
 - (analytic functors)
- Regular expressions
- It is possible to combine the attributes

```
[tag="R.+"][[lemma="Praha."*]]
```

Displaying

- Selection of attributes
 - for KWIC
 - for all positions
- Changing range - number of concordances
 - from beginning / end / middle
 - randomly
- Information about the source of the text
- Changing context
 - Wider context in extra region

Sorting and Filtering

- Sorting according to
 - kwic (key word in context)
 - left or right context
 - combination
- Filters
 - positive
 - negative

Statistics

- Frequency distribution
 - according to selected attributes
- Collocations
 - absolute frequency
 - relative frequency
 - Mutual information
 - t-score

$$mi(x, y) = \log_2 \frac{N \cdot f(x, y)}{f(x) \cdot f(y)}$$

$$T = \frac{\left(f(x, y) - \frac{f(x) \cdot f(y)}{N} \right)}{\sqrt{f(x, y)}}$$


$$ARF = 1/v \sum_{i=1}^v \min(d_i, v)$$

– distribution overview + Average Reduced Frequency

Netgraph – a Tool for Searching in Prague Dependency Treebank 2.0

- Client–server architecture
- Authentication of users
- Subcorpus definition
- Graphic creation of a query
- Searching in the treebank according to the query
- Viewing the result trees
- Basic statistics

Viewing the Result



A Query Creation

The screenshot shows the Netgraph interface for query creation. It includes a 'query tree' window at the top with nodes 'functor=PREB', 'functor=ACT', 'functor=EF', and 'functor=ADDR'. Below it is a 'possible values' window with categories like 'attribute', 'reference', 'factory', and 'value'. A 'query' field contains the expression: [functor=PRED][!functor=ACT][!functor=EFF].[!functor=ADDR]'. The bottom part of the interface includes tabs for 'Files', 'Query', 'Trees', and 'Debug', along with buttons for 'load', 'save', 'clear', and 'select trees by the query'.


[functor=PRED][!functor=ACT][!functor=EFF].[!functor=ADDR])

Meta-attributes

- Additional power to the query language
- Attributes not present in the corpus
- Treated like normal attributes
 - **_transitive** (*transitive edge*)
 - **_optional** (*optional node*)
 - **#sons** (*exact number of sons*)
 - **depth** (*distance from the root*)
 - ...


- Different order of nodes; additional sons of the **PREDicate**

An Example Query




- A query with optional **CON**junction node
- Two possible types of result – with and without the optional node

An Example of a Wrong Query




- A wrong attempt to set negation in the query
- We do not want the **PATient** there at all
- But the query node matches with **PREC**

A Correct Negation




- A correct way how to set negation in the query
- We define that there are exactly zero **PATients** as sons of the **PREDicate**

Yet Another Example Query



- Looking for a small tree (root of the query)
- **PATient** is a coreferential node of **ACTor** and is on the left side from the **ACTor**

A Result Tree



<http://quest.ms.mff.cuni.cz/netgraph>

Part 6

DATA:
The Prague Mark-up Language

Introduction

In PDT 2.0 and some related annotation projects, we:

- ▶ use several (interlinked) annotation levels
- ▶ introduce various types of annotation: linear, tree-structured, ...
- ▶ apply one annotation schema to different languages
- ▶ sometimes use project-specific variants/flavors of existing annotations or annotation schemas
- ▶ use something called “*annotation dictionaries*”

Our goal is to represent all data resulting from these projects coherently, in a uniform manner.

- ▶ We need a meta-format (from which we may derive specific formats for our annotation schemas and layers)
- ▶ XML is known to be an excellent meta-format, but still too generic to ensure uniformity of representation
- ▶ thus, we need another layer of abstraction, between the “generic” (XML) and the “specific” (data-specific format)

XML-Based Format of PDT 2.0 Data

Petr Pajáš

ÚFAL, MFF, Charles University, Prague

November 29, 2006

November 29, 2006 / 38

Petr Pajáš (Charles University)


PML – Prague Markup Language

November 29, 2006 / 38

Requirements

- ▶ Uniformity of representation
- ▶ Stand-off annotation principles
- ▶ Unified cross-referencing and linking system
- ▶ Linearity and structure
- ▶ Structured attributes
- ▶ Handling ambiguity
- ▶ Human-readability
- ▶ Extensibility
- ▶ XML based
- ▶ Description language

PML – Prague Markup Language



PML – Prague Markup Language (2)

Every annotation layer has a PML-based format specified by something called *PML schema*.

- ▶ PML schema
 - ▶ A *data format description language*.
 - ▶ Formalizes the “annotation schema” for a particular layer
 - ▶ Defines the *annotation structure*
 - ▶ Assigns PML roles to certain pieces of annotation.
- ▶ annotation structure
 - ▶ data structure built from abstract data types, such as:
 - ▶ atomic values, attribute-value structures, lists, alternatives, etc.
- ▶ PML role
 - ▶ identifies a piece of annotation as a bearer of some additional higher-level property, such as being a node of a tree, being a unique identifier, etc.

XML documents conforming to a PML schema are called PML instances.

Data types – overview

- ▶ **Atomic (simple)**
 - ▶ cdata
 - ▶ enumerated
 - ▶ constant
- ▶ **Complex**
 - ▶ structures
 - ▶ containers
 - ▶ lists
 - ▶ alternatives
 - ▶ sequences

```
PML schema declaration
```

```
<...>hall@234</...>
<...>12.7843E-2</...>
<...>17</...>
<...>-9223372054775808</...>
→ <...>1999-05-31</...>
<...>13:20:00.000</...>
<...>ar6!7z@r# d0t&</...>
...
...
```

PML – Prague Markup Language (3)

Processing PML

PML instances can be processed using:

- ▶ arbitrary XML-oriented tools (based on DOM, XPath, etc.)
- ▶ format-specific tools with hard-wired knowledge about the XML vocabulary of a particular PML-based format
- ▶ intelligent generic tools aware of PML-schema:
 - ▶ data type declarations → optimal in-memory representation (data binding)
 - ▶ role assignment → adequate way of presenting the annotation to the user and providing some extra features (indexes, etc.)

Validation

- ▶ using conventional validators for XML such as xmllint or jing.
- ▶ (PML schema translates to a Relax NG – via XSLT)

Data types – atomic (1)

cdata type

- ▶ literal character-based content
- ▶ no explicitly marked internal structure
- ▶ value format can be restricted
- ▶ current formats include most W3C Schema simple types

PML schema declaration

```
<cdata format="token"/>
<cdata format="float"/>
<cdata format="positiveInteger"/>
→ <cdata format="long"/>
<cdata format="date"/>
<cdata format="time"/>
<cdata format="any"/>
...
...
```

Data types – atomic (2)

enumerated type

Literal values from a fixed finite set.

```
PML schema declaration
<type name="boolean.type">
  <choice>
    <value>TRUE</value>
    <value>FALSE</value>
  </choice>
</type>
```

instance example

```
<...>TRUE<...>
```

constant

A fixed constant value.

```
PML schema declaration
<type name="root-node.type">
  <structure>
    <member name="node-type">
      <constant>root</constant>
    </member>
    ...
  </structure>
</type>
```

instance example

```
<...>
  <!-- no need to use explicitly -->
  ...
</...>
```

Data types – complex (2)

container

- attaches attributes to a single central value (content)
- attributes are name-value pairs with atomic values
- the set of attributes is declared in the schema
- content can be atomic or complex other than container or structure

```
PML schema declaration
<type name="word.type">
  <container>
    <attribute name="id" role="#ID">
      <cdata format="ID"/>
    </attribute>
    <cdata format="token"/>
  </container>
```

instance example

```
<... id="w-23">Walking<...>
```

Data types – complex (1)

Attribute-value structure (AVS)

- consists of a fixed set of attribute-value pairs (called members)
- values can be atomic or complex
- value type of each member is declared in the PML schema
- members can be optional or required
- atomic-valued members can be rendered as attributes

PML schema declaration

```
<structure>
  <member name="id" as_attribute="1">
    <cdata format="ID" role="#ID"/>
  </member>
  <member name="form" required="1">
    <cdata format="token"/>
  </member>
  <member name="lemma">
    <cdata format="token"/>
  </member>
  <member name="tag" type="tagset.type"/>
</structure>
```

example instances

```
<... id="m-23">
  <form>walking</form>
  <lemma>walk-1</lemma>
  <tag>VBG</tag>
</...>
  <... id="m-24">
  <form>away</form>
</...>
```



Data types – complex (3)

list

- aggregate zero or more values of a certain type
- can be ordered or unordered (sets).
- reserved tag <LM> used for list values
- single <LM> can sometimes be omitted (list folding)

PML schema declaration

```
<type name="sent.type">
  <list ordered="1" type="word.type">
  </list>
</type>
```

example instance (several values)

```
<...>
  <LM id="w-34">Flies</LM>
  <LM id="w-35">like</LM>
  <LM id="w-36">an</LM>
  <LM id="w-37">arrow</LM>
  <LM id="w-38">.</LM>
</...>
```

example instance (single value)

```
<...>
  <LM id="w-34">Flies</LM>
</...>
```

can fold into:

```
<... id="w-34">Flies</...>
```

Data types – complex (3)

Data types – complex (4)

alternative

- ▶ aggregates values in parallel, i.e. as alternative annotations.
 - ▶ reserved tag `<AM>` used for alternative values
 - ▶ single `<AM>` can be omitted (folding)

instance example

```
< . . . >
<AM id='m-34'>
  <form>flies</form>
  <lemma>fly-1</lemma>
  <tag>VBZ</tag>
</AM>
<AM id='m-34A'>
  <form>flies</form>
  <lemma>fly-2</lemma>
  <tag>NNNS</tag>
</AM>
</ . . . >
```

↑

PML schema declaration

PML roles

- | | |
|------|---|
| ID | assigned to members or attributes uniquely identifying an AVS or a container within a PML instance |
| KNIT | assigned to links suitable for merging two annotation layers in such a way that the referred object is embedded into the referring object |

marks lists or sequences of dependency or constituency trees

identifies nodes of dependency or constituency trees

CHILDNODES identifies the member of a node (of a dependency or constituency tree) containing the list of its child nodes

used to identify numerical values which determine a total ordering on a tree

Links

卷之三

YES

assigned to members or attributes uniquely identifying an AVS or a container within a PML instance

links suitable for merging two annotation layers in such a way that the referred object is embedded into the referring object

- ▶ Currently only ID-based links are supported
 - ▶ Other types of links represented in PML on a per-application basis

Induced final

- ▶ Cross-references within a single PML instance

- ▶ Links to other instances
- ▶ Typically many links to only few target instances

- Therefore F-M links have two parts:
 - ▶ the specification of the target instance – a label (ID) associated with the target instance in the referring instance header
 - ▶ the ID of the target object

Links to non-PML data

Links - examples

Associating target URLs with IDs in the referring instance header


```
<references>
  <reffile id="a" href="#doc73.a"/>
  <reffile id="v" href="http://mysite/vallex.xml"/>
</references>

Examples of ID-based links
<core_rf>t-node-232</core_rf> — link to the same file
<val_frame_rf>v#f2234</val_frame_rf> — link to http://mysite/vallex.xml
<lex_rf>a#doc73-w5</lex_rf> — links to doc73.a
<aux_rf>
  <LM>a#doc73-w3</LM>
  <LM>a#doc73-w4</LM>
</aux_rf>
```

Petr Pajas (Charles University) PML – Prague Markup Language November 29, 2006 17 / 38

Extendibility

Data fields of any type may be upgraded to allow ambiguity:



PML allows to upgrade or extend the data model in many ways while retaining the XML representation of the existing data.

- ▶ alternative folding
- ▶ list folding
- ▶ container transparency
- ▶ structure to sequence conversion
- ▶ structure and sequence extendibility

Currently no guidelines.

Example of possible PML representation of pointers to an audio file:

```
<references>
  <reffile id="au1" href="spk1_129.ogg"/>
</references>
...
<w id="w-12941">
  <token>_SIL_</token>
<audio>
  <time_start>600000</time_start>
  <time_end>4700000</time_end>
  <file_rf>au1</file_rf>
</audio>
</w>
```

Petr Pajas (Charles University) PML – Prague Markup Language November 29, 2006 18 / 38

Extendibility – singleton alternative minimization

Extendibility – singleton list minimization


By the „uniformity of representation“ principle, we get the same for lists.

Upgrading a value to a lists of values:



Extendibility – container transparency

Add attribute annotation to flat data, lists, etc.




Modularization

Allows to easily derive one PML schema from another.

- revision numbering
PML schemas can be assigned revision numbers of the form X.Y.Z...
↳ **<import>** instruction
Copies type declarations from a different PML schema with revision restrictions.
- <derive> instruction
Derive types from a previously declared or imported AVS structure, container, sequence, or enumerated type.
- simplified PML schemas
pml_simplify - a PML schema preprocessor, resolves all <import> and <derive> instructions
Useful e.g. before XSLT 1.0 transformations.

Validation

- Conformance of PML schemas to the spec can be verified via Relax NG and Schematron.
- Simplified PML schemas can be XSLT-transformed into Relax NG for data validation purposes.
Many validators for Relax NG exist.
The script validate_pml automates all the necessary steps.



PML schema for a-layer (1)

```
...  
<pml-schema  
    xmlns="http://ufal.mff.cuni.cz/pdt/pml/schema/" version="1.1">  
    <revision>1.0.3</revision>  
    <description>PDT 2.0 analytical trees</description>  
    <reference name="mdata" readas="dom"/>  
    <reference name="wdata" readas="dom"/>  
  
    <import schema="mdata-schema.xml" type="m-node.type" />  
    <minimal_revision>1.0.3</minimal_revision>  
    <import schema="mdata-schema.xml" type="bool.type" />  
  
    <derive type="m-node.type">  
        <structure name="m-node">  
            <member name="id" as_attribute="1" role="#ID" required="1">  
                <cdata format="PMLREF"/>  
            </member>  
        </structure>  
    </derive>  
    ...
```

Petr Pajáš (Charles University) PML – Prague Markup Language November 29, 2006 29 / 38

PML schema for a-layer (2)

```
...  
<root name="adata" type="a-adata.type" />  
<type name="a-adata.type" />  
<structure>  
    <member name="meta" required="0" type="a-meta.type" />  
    <member name="trees" role="#TREES" required="1" />  
    <list type="a-root.type" ordered="1" />  
    </member>  
    </structure>  
</type>  
  
<type name="a-meta.type" />  
<structure>  
    <member name="annotation_info" />  
    <structure name="a-annotation-info">  
        <member name="version.info"><cdata format="any" /></member>  
        <member name="desc"><cdata format="any" /></member>  
    </structure>  
    </member>  
    </structure>  
</type>  
...
```

Petr Pajáš (Charles University) PML – Prague Markup Language November 29, 2006 30 / 38

PML schema for a-layer (3)

```
...  
<type name="a-root.type" />  
<structure role="#NODE" name="a-node" />  
<member name="id" role="#ID" as_attribute="1" required="1" />  
    <cdata format="ID" />  
</member>  
<member name="s_rf"><cdata format="PMLREF" /></member>  
<member name="afun"><constant>AuxS</constant></member>  
<member name="ord" role="#ORDER" required="1" />  
    <cdata format="nonNegativeInteger" />  
</member>  
<member name="children" role="#CHILDNODES" />  
    <list type="a-node.type" ordered="1" />  
</member>  
</structure>  
</type>
```

Petr Pajáš (Charles University) PML – Prague Markup Language November 29, 2006 31 / 38

PML schema for a-layer (4)

```
...  
<type name="a-node.type" />  
<structure role="#NODE" name="a-node" />  
<member name="id" role="#ID" as_attribute="1" required="1" />  
    <cdata format="ID" />  
</member>  
<member name="m_rf" role="#KNIT" type="m-node.type" />  
    <cdata format="PMLREF" />  
</member>  
<member name="afun" type="a-afun.type" required="1" />  
    <member name="is_member" type="bool.type" />  
    <member type="bool.type" name="is_parenthesis_root" />  
    <member name="ord" role="#ORDER" required="1" />  
    <cdata format="nonNegativeInteger" />  
</member>  
<member name="children" role="#CHILDNODES" />  
    <list type="a-node.type" ordered="1" />  
</member>  
</structure>  
...
```


Petr Pajáš (Charles University) PML – Prague Markup Language November 29, 2006 32 / 38

Sample a-layer instance

```

<adata xmlns="http://ufal.mff.cuni.cz/pdt/pml/">
  <head>
    <schema href="adata_schema.xml" />
  </head>
  <references>
    <reffile id="m" name="mdata" href="sample4.m.gz" />
    <reffile id="w" name="wdata" href="sample4.w.gz" />
  </references>
  </adata>
  <annotation_info>
    <desc>Manual annotation</desc>
    </annotation_info>
  </meta>
  <trees>
    <LM id="a-p1s1"> . . .
    <LM id="a-p1s2"> . . .
  </trees>
  ...
</adata>
```

Sample PDT 2.0 instance (a+m-layer)



Sample PDT 2.0 instance (a-layer)

```

<LM id="a-p1s1">
  <s.rf>#m-p1s1</s.rf>
  <ord></ord>
  <children>
    <LM id="a-p1s1w2">
      <m.rf>#m#-p1s1w2</m.rf>
      <afun>Pred</afun>
      <ord></ord>
      <children>
        <LM id="a-p1s1w1">
          <m.rf>#m#-p1s1w1</m.rf>
          <afun>Sh</afun>
          <ord></ord>
          <children>
            <LM id="a-p1s1w3">
              <m.rf>#m#-p1s1w3</m.rf>
              <afun>AuxX</afun>
              <ord></ord>
              <children>
                <LM id="a-p1s1w4">
                  <m.rf>#m#-p1s1w4</m.rf>
                  <afun>Obj</afun>
                  <ord></ord>
                  <children>
                    <LM id="a-p1s1w2">
                      <m.rf>#m#-p1s1w2</m.rf>
                      <afun>Sh</afun>
                      <ord></ord>
                      <children>
                        <LM id="a-p1s1w1">
                          <m.rf>#m#-p1s1w1</m.rf>
                          <afun>AuxP</afun>
                          <ord></ord>
                          <children>
                            <LM id="a-p1s1w4">
                              <m.rf>#m#-p1s1w4</m.rf>
                              <afun>Obj</afun>
                              <ord></ord>
                            </LM>
                          </children>
                        </LM>
                      </children>
                    </LM>
                  </children>
                </LM>
              </children>
            </LM>
          </children>
        </LM>
      </children>
    </LM>
  </children>
</LM>
</a-layer>
```

Petr Pajas (Charles University) November 29, 2006 34 / 38

Sample PDT 2.0 instance (a+m+w-layer)

```

<LM id="a-p1s1">
  <s id="m-p1s1w1">
    <m id="m-p1s1w1">
      <src.rf>manual</src.rf>
      <ord></ord>
      <children>
        <LM id="a-p1s1w2">
          <m.rf>#m#-p1s1w2</m.rf>
          <afun>Pred</afun>
          <ord></ord>
          <children>
            <LM id="a-p1s1w1">
              <m.rf>#m#-p1s1w1</m.rf>
              <afun>Sh</afun>
              <ord></ord>
              <children>
                <LM id="a-p1s1w2">
                  <m.rf>#m#-p1s1w2</m.rf>
                  <afun>Vstoupit.W</afun>
                  <ord></ord>
                  <children>
                    <LM id="a-p1s1w1">
                      <m.rf>#m#-p1s1w1</m.rf>
                      <afun>Sh</afun>
                      <ord></ord>
                      <children>
                        <LM id="a-p1s1w3">
                          <m.rf>#m#-p1s1w3</m.rf>
                          <afun>AuxP</afun>
                          <ord></ord>
                        </LM>
                      </children>
                    </LM>
                  </children>
                </LM>
              </children>
            </LM>
          </children>
        </LM>
      </children>
    </LM>
  </children>
</LM>
</a-layer>
```

Petr Pajas (Charles University) November 29, 2006 34 / 38

Sample PDT 2.0 instance (a+m+w-layer)

```

<LM id="a-p1s1">
  <s id="m-p1s1w1">
    <m id="m-p1s1w1">
      <src.rf>manual</src.rf>
      <ord></ord>
      <children>
        <LM id="a-p1s1w2">
          <m.rf>#m#-p1s1w2</m.rf>
          <afun>Pred</afun>
          <ord></ord>
          <children>
            <LM id="a-p1s1w1">
              <m.rf>#m#-p1s1w1</m.rf>
              <afun>Sh</afun>
              <ord></ord>
              <children>
                <LM id="a-p1s1w2">
                  <m.rf>#m#-p1s1w2</m.rf>
                  <afun>Vstoupit.W</afun>
                  <ord></ord>
                  <children>
                    <LM id="a-p1s1w1">
                      <m.rf>#m#-p1s1w1</m.rf>
                      <afun>Sh</afun>
                      <ord></ord>
                      <children>
                        <LM id="a-p1s1w3">
                          <m.rf>#m#-p1s1w3</m.rf>
                          <afun>AuxP</afun>
                          <ord></ord>
                        </LM>
                      </children>
                    </LM>
                  </children>
                </LM>
              </children>
            </LM>
          </children>
        </LM>
      </children>
    </LM>
  </children>
</LM>
</a-layer>
```

Petr Pajas (Charles University) November 29, 2006 34 / 38

Sample PDT 2.0 instance (a+m+w-layers knitted)

```
a-layer
<LM id="a-p1s1w1">
<s .rf>#m-p1s1w2</s .rf>
<ord0><ord>
<children>
<LM id="a-p1s1w2">
<afun>m#m-p1s1w2</m.rf>
<ord><ord>
<children>
<LM id="a-p1s1w1">
<afun>Sb</afun>
<ord1><ord>
</LM>
<LM id="a-p1s1w3">
<m.rf>#m-p1s1w1</m.rf>
<afun>Sb</afun>
<ord3><ord>
<children id="a-p1s1w4">
<m.rf>#m-p1s1w4</m.rf>
<afun>Obj</afun>
<ord4><ord>
</children>
</LM>
<LM>
<children>
</LM>
</LM>
```

→ → → →

After knitting

```
m-layer
<s id="m-p1s1w1">
<m id="m-p1s1w1">
<srcc.rf>manual</srcc.rf>
<w id="w#w-p1s1w1">
<token>Prímerí</token>
</w>
<form>Prímerí</form>
<lemma>prímerí</lemma>
<tag>NNNS1----A---</tag>
</m>
<afun>Sb</afun>
<ord>1</ord>
</LM>
```

↑ ↑ ↑ ↑

w-layer

```
<s id="m-p1s1w1">
<m id="m-p1s1w1">
<srcc.rf>manual</srcc.rf>
<w id="w#w-p1s1w1">
<token>Prímerí</token>
</w>
<form>Prímerí</form>
<lemma>prímerí</lemma>
<tag>NNNS1----A---</tag>
</m>
<afun>Sb</afun>
<ord>1</ord>
</LM>
```

↑ ↑ ↑ ↑

Petr Pajas (Charles University) PML – Prague Markup Language November 29, 2006 34 / 38

Petr Pajas (Charles University) PML – Prague Markup Language November 29, 2006 35 / 38

Future development

- foreign namespaces
 - allow XML data from non-PML namespaces within PML instance (*MathML, XLink, RDF, ...*)
- meta-data
 - uniform representation of meta-data (via RDF)
- schema annotation
 - similar to what W3C schema has
- new roles
 - Current set of roles doesn't cover all situations, e.g. *lexicons*
 - foreign XML, other media (text, audio, video, graphics, ...)
- guidelines for more types of links
 - translate PML schemas into a ready-to-use library with optimal memory representation, validation, parser, serializer, indexing, etc.
- automatic data-binding and API generation

Technical issues with multi-layered annotations in PML

PML homepage

- PDT 2.0 data are distributed in gzip-compressed forms. Same problem: decompress removes the .gz suffix, which renames the instance. Again, references have to be fixed.
- PDT 2.0 data are distributed in gzip-compressed forms. Same problem: decompress removes the .gz suffix, which renames the instance. Again, references have to be fixed.
- PML spec (with many examples)
- Relax NG schema for PML schema
- tools (simplification, validation, ...)
- updated PDT 2.0 schemas
- links

Petr Pajas (Charles University) PML – Prague Markup Language November 29, 2006 35 / 38

Petr Pajas (Charles University) PML – Prague Markup Language November 29, 2006 36 / 38

Part 7

TOOLS (continued): Automatic processing of data

**STYX
- an electronic exercise book of
Czech**

Prague Treebanking for Everyone

run_all from PDT

Located in `tools/machine-annotation/run_all`.

- Tokenization of the input plain text and segmentation into sentences.
 - Morphological analysis and tagging (morphological disambiguation).
 - Dependency parsing
 - Analytical (dependency) function assignment for all nodes of the parsed tree.

29th November 2006

Jan Štěpánek

Automatic Processing of Data

run_all from PDT

Tokenization and segmentation

- Problems with full-stop (".") in Czech.
- Tested on `amw` data:
 - Segmentation:
 - precision 98.0 %, recall 91.4 %, F-measure 94.6 %.
 - Tokenization:
 - precision 100.0 %, recall 99.2 %, F-measure 99.6 %.

run_all from PDT

Morphological analysis

- All possible lemmas and tags.
- Dictionary of 350,000 entries, 12 million Czech word forms.
 - Error rate: 2.5 % (foreign names and typos).

[run_all from PDT](#)

Morphological tagger

- Maximum entropy approach with greedy incorporation of selectors.
- Tagging – 93.08 % accuracy on evaluation test data.

[run_all from PDT](#)

Parsing

- Czech adaptation of the parser of Michael Collins — dependency based.
- Only shorter sentences (up to 60 words).
- Evaluation test data: 81.6 % parents assigned correctly (both training and test data tagged machiney).

[run_all from PDT](#)

Analytical function assignment

- Decision tree approach (Quinlan's C5 classifier translated to perl)
- Uses **btred**.
- Precision around 92 %.

[run_all from PDT](#)

Conversion to PML

- All the previous steps use deprecated CSTS format.
- Conversion script uses **btred**.

morph_chain from CAC

Dealing with the Structural Annotation btred

Features (same as those of TrEd):

- Located in tools/morph_chain.
- Hidden Markov models — trained by Viterbi algorithm + averaged perceptron for evaluating transitions between HMM states (Collins)
- Trained on PDT: 91.8 % (93.1)

Why btred?

Dealing with the Structural Annotation

Why btred?

- Object-oriented tree representation — a rich repertory of basic functions for tree traversing and for many other basic operations on trees + several highly non-trivial functions suitable for linguistically motivated traversing of trees (e.g. solving the coordination relations).
- Reasonable stability because of long-time experience (development of PDT).
- Network (parallel) version (not for MS Windows).
- Powerful and fast search-engine (pipes).

Basic syntax:

```
btred -e <code> file(s) OR btred -I macro_file file(s)

$ btred -e 'writeln("Hello world!"); sample0.a.gz'
BTRED: Trying /export/common/lib/tred
Config file: /home/stepanek/.tredrc
BTRED: Resource path: /home/stepanek/tred/resources/
BTRED: Reading macros from /usr/tred/tred.mac...
BTRED: done.

BTRED: <script>
package TredMacro;
sub _btred_eval_ {
    writeln("Hello world!");
}

;

</script>
BTRED: Processing: sample0.a.gz (1/1)
Hello world!
BTRED: Done.
```

Dealing with the Structural Annotation

Simplest examples

Dealing with the Structural Annotation

Simple examples (2)

```
Traversing trees:  
$ btred -QTe 'writeln($a++); sample0.a.gz  
...  
52  
53  
  
Traversing trees and nodes:  
$ btred -QNTe 'writeln($a++); sample0.a.gz  
...  
864  
865  
  
More files:  
$ btred -QNTe 'writeln($a++); sample*.a.gz  
...  
7813  
7814
```

Dealing with the Structural Annotation

Simple examples (2)

```
Simple attributes:  
$ btred -QNTe 'writeln($this->{afun}), sample0.a.gz  
...  
Atr  
AuxK  
  
Structured and list attributes  
$ btred -QNTe 'writeln($this->attr("m/form")), sample0.a.gz  
...  
založení  
OSN  
  
$ btred -QNTe 'my @ids = ListV($this->attr("coref.text.rf"));  
if (@ids){  
    writeln(PML_T::GetNodeByID($ids[0])->{t_lemma});  
}  
', sample*.t.gz  
...  
#PersPron  
Chodura
```

Dealing with the Structural Annotation

Examples (2)

```
perl functions grep and map — print verbs and their objects:  
$ btred -QNTe 'if($this->attr("m/tag") =~ /~V/ ) {  
    writeln join " ",  
    $this->attr("m/form"),  
    map {$_->attr("m/form")}  
        grep {$_->{afun} eq "Obj"} $this->children;  
}', sample1.a.gz  
...  
Nehodlá vyjadřovat  
vyjadřovat  
dokončil šetření  
předal spis zastupitelství
```

Similarly: children, parent, lbrother...

Dealing with the Structural Annotation

Complex examples (2)

Effective children and parents — what semantical part of speech are the parents of actors and how often:

```
$ btred -QNTe ,
my $par;
$par = join(" ", 
map( {
    $_->attr("gram/sempos")
} PML_T::GetEParents())
),writeln($par) if $this->{functor} eq "ACT"
, sample*.t.gz | sort | uniq -c | sort -n
...
4 v v v
5 adj.denot
25
30 v v
108 n.denot
117 n.denot.neg
667 v
```

Dealing with the Structural Annotation

Complex examples (2)

Crossing layer boundaries — count all actors expressed by a noun in nominative (1st case):

```
$ btred -QNTe 'writeln() if $this->{functor} eq "ACT"
and ! $this->{is-generated}
and first {
    my $t = $_->attr("m/tag");
    $t =~ /N...1/
} PML_T::GetANodes($this)
, sample*.t.gz | wc -l
422
```

Dealing with the Structural Annotation

Searching and viewing results

TrEd function FPosition():

```
$ btred -QNTe 'FPosition()
if $this->{t_lemma} =~ /.*-/ , sample*.t.gz
sample9.t.gz#14.22
$ btred -I macro-that-uses-FPosition *.t.gz |
tred -1-
```

Crawling through all the tectogrammatical nodes by **btred** takes about 10 minutes. Most time is spent by *opening* and *parsing* the data.

Possible solution: read all the data just once and keep them in the memory.

Problem: not enough memory.

Solution: distribute the data among several computers.

ntred (network-tred): **btred** servers + *hub*

Prague Dependency Treebank as an exercise book of Czech

ntred requirements:

- Cannot run on MS Windows (problems with net sockets).
- All the computers running btred-servers must share a filesystem.
- Password-free access to all the computers is needed.
- Some macros have to be adjusted (e.g. overall statistics).

Ondřej Kučera

Contents

1. Introduction (motivation, PDT, implementation)

2. Filtering sentences

3. Transformations of trees

4. STYX: FilterSentences, Charon, StyX

Motivation

- children of today use computers regularly
 - games, web surfing, chatting, writing, drawing
- why couldn't they parse sentences or determine parts of speech?

Building an exercise book

Building an exercise book

Manually

- extremely hard
 - choose (make up) the sentences
 - annotate them
- considerably limited number of sentences
- often too simple sentences not reflecting the real usage of the language

Automatically

- if we have annotated data
 - the work of choosing the sentences and annotating them is already done
 - the data in corpus reflect the real usage of the language
 - the number of sentences corresponds to the size of the corpus
 - PDT

Prague Dependency Treebank

- annotated on four layers (word, morphological, analytical, tectogrammatical)
- inner data format: PML (Prague Markup Language) – based on XML

PDT vs. school syntax

- annotation rules of PDT allow to process any sentence
 - ⇒ filtering sentences
- Analytical layer of PDT differs from the school syntax in many ways
 - ⇒ transformations of analytical trees

Filtering sentences

Filtering in numbers

- nine different filters
- starting number of sentences: 49,442
- after application of the filters: 11,705
- about 23.7% sentences kept


Transformation of trees

- three basic transformations

- particular transformations consist of
 - combining of the three basic transformations
 - rules for modification of the syntactic functions

Transformations of trees

Example



Implementation

Java



- high-level language with number of mechanisms protecting programmers “against themselves”
- portability
- presence of SWT library

SWT

- Standard Widget Toolkit
- provides native look and feel of graphical user interface
- speed

Implementation


Implementation



STYX: FilterSentences, Charon, Styx

FilterSentences


- used for applying the filters
- reads data in PML format
- each sentence is tested by a filter
- output data contains the sentences that the filter kept
- output again in PML format




Charon

Charon

- “administrative” program
- loads all sentences available
- the user selects sentences that he or she wants to have in the exercise
- in the end the user saves the exercise



Charon





Styx

- exercise book itself
- user loads an exercise previously created and saved in Charon

Styx


Styx



Styx

Questions

and perhaps some answers...



Part 8

DATA: More Prague Treebanks

The Prague Czech-English Dependency Treebank (part 8.1)



Jan Hajíč
Institute of Formal and Applied Linguistics
School of Computer Science
Faculty of Mathematics and Physics
Charles University, Prague
Czech Republic

VMC Tutorial: The Prague Dependency Treebank

1

The Goal: Parallel, Annotated Treebank



- Parallel corpora
- Comparative/contrastive and translation studies
- Semantics
- Other “linguistic research goals”
- Machine Translation
 - “Training” material
 - Human-translated texts
 - Testing material
 - Evaluation – human, automatic

Nov. 27-28, 2006

VMC Tutorial: The Prague Dependency Treebank

2

The PCEDT

- One of “family” of PDT-like treebanks
- Texts:
 - Wall Street Portion of the Penn Treebank, ver. III
 - Czech translation (manual) of the above
- Size
 - 1.2 million words, ~50,000 sentences
- Annotation
 - All 4 layers as in PDT: tokens, morphology, syntax, tectogrammatical representation

Nov. 27-28, 2006

VMC Tutorial: The Prague Dependency Treebank



Penn Treebank



- University of Pennsylvania, 1993
- Linguistic Data Consortium
- Wall Street Journal texts
 - 1989-1991
 - Financial (most), news, arts, sports
 - 2499 documents in 25 sections
- Annotation
 - POS (Part-of-speech tags)
 - Syntactic “bracketing” + bracket (syntactic) labels
 - (Syntactic) Function tags

VMC Tutorial: The Prague Dependency Treebank

3

VMC Tutorial: The Prague Dependency Treebank

4

VMC Tutorial: The Prague Dependency Treebank

Penn Treebank Example


- The diagram shows a complex dependency parse tree. The root node is S, which contains NP-SBJ and a punctuation mark (.). NP-SBJ contains NNP Pierre and NNP Vinken. ADJP contains NP (CD 61) and NNS years. The NNS node has a dependency on the NP node. JJ old is a child of ADJP. VP contains MD will and VP (AVBing). AVBing contains DT a and NP (T the) and NN board. NP (T the) contains T the. PP (CLR (IN as)) contains CLR (IN as) and NP (DT a) and JJ nonexecutive and NN director. NP (DT a) is a child of PP (CLR (IN as)). NP-TMP contains DT a and JJ nonexecutive and NN director. CD 29 is a child of NP-TMP. All nodes are labeled with their part-of-speech tags in parentheses.

/MC Tutorial: The Prague Dependency Treebank

Nov. 27-28, 2006

Penn Treebank Example: Sentence Tree

- Phrase-based tree representation:



Nov. 27-28, 2006

8

PDT Layers of Annotation

electogrammatical
structure

MC Tutorial: The Prague Dependency Treebank

Nov 27-28, 2000

Parallel Czech-English Annotation

- English text -> Czech text (human translation)
 - Czech side (goal): all layers manual annotation
 - English side (goal):
 - Morphology and surface syntax: technical conversion
 - Penn Treebank style -> PDT Analytic layer
 - Tectogrammatical annotation: manual annotation
 - (Slightly) different rules needed for English
 - Alignment

Nov. 27-28 2006

8



Parallel Czech-English Annotations

- English text -> Czech text (human translation)
 - Czech side (goal): all layers manual annotation
 - English side (goal):
 - Morphology and surface syntax: technical conversion
 - Penn Treebank style -> PDT Analytic layer
 - Tectogrammatical annotation: manual annotation
 - (Slightly) different rules needed for English
 - Alignment

8

YMC Tutorial: The Prague Dependency Treebank

Human Translation: WSJ Texts

- Hired translators / FCE level
- Specific rules for translation
 - Sentence per sentence only
 - ...to get simple 1:1 alignment
 - Fluent Czech at the target side
 - If a choice, prefer "literal" translation
 - The numbers:
 - English tokens: 1173766
 - Translated to Czech:
 - Revised/PCEDT 1.0: 487929
 - (now: 1097471)

Nov. 27-28, 2006 VMC Tutorial: The Prague Dependency Treebank

9

Head Determination Rules

- Exhaustive set of rules
 - By J. Eisner + M. Cmejrek/J. Curin
 - 4000 rules (non-terminal based)
 - Ex.: (S (NP-SBJ VP .)) → VP
 - Additional rules
 - Coordination, Apposition
 - Punctuation (end-of-sentence, internal)
- Original idea (possibility of conversion)
 - J. Robinson (1960s)

Nov. 27-28, 2006 VMC Tutorial: The Prague Dependency Treebank

11


English Annotation POS and Syntax

- Automatic conversion from Penn Treebank
 - PDT morphological layer
 - From POS tags
 - PDT analytic layer
 - From:
 - Penn Treebank Syntactic Structure
 - Non-terminal labels
 - Function tags (non-terminal "suffixes")
 - 2-step process
 - Head determination rules
 - Conversion to dependency + analytic function

Nov. 27-28, 2006 VMC Tutorial: The Prague Dependency Treebank

10

Example: Head Determination Rules



Nov. 27-28, 2006 VMC Tutorial: The Prague Dependency Treebank

12

Conversion to Analytic Structure, Functions


- Analytic Function assignment (conversion)
- Rules
 - based on functional tags:
 - SBJ Sb
 - PRD Pnom
 - DTV Obj
 - ADV Adv
 - EXT Adv
 - MINR Adv
 - PUT Adv
 - TMP Adv
 - Ad-hoc rules (if functional tags missing)
 - Lemmatization (years → year)

Nov. 27-28, 2006 VMC Tutorial: The Prague Dependency Treebank

Nov. 27-28, 2006 VMC Tutorial: The Prague Dependency Treebank

13

Example: Conversion to Analytical Structure, Functions



14

English PDT-style Annotation

- Morphology and Syntax
 - By conversion
- Tectogrammatical annotation
 - Manual
 - Pre-annotation
 - Transformation from Penn Treebank & Propbank (Palmer, Kingsbury)
 - Valency
 - From Propbank Frame Files
 - Starting now

Nov. 27-28, 2006 VMC Tutorial: The Prague Dependency Treebank

Nov. 27-28, 2006 VMC Tutorial: The Prague Dependency Treebank

Nov. 27-28, 2006 VMC Tutorial: The Prague Dependency Treebank

Nov. 27-28, 2006 VMC Tutorial: The Prague Dependency Treebank


15

Czech PDT-style Annotation

- All layers
 - (morphology, analytic, tectogrammatical)
- So far...
 - Automatic
 - Manual annotation
 - Starting now
 - Top-down
 - Tectogrammatical first (lower layers automatically)
 - ... then analytic structure and morphology

16

Analytical Pair En - Cz



Those current holders would also receive minority interests in the new company.


VMC Tutorial: The Prague Dependency Treebank

17

Nov 27-28 2006

18


Analytical Pair En - Cz



According to his opinion UAL's executives were misinformed about the financing of the original transaction.

18

Tectogrammatical Pair En - Cz



According to his opinion UAL's executives were misinformed about the financing of the original transaction.

Podle jeho názoru byly řídící osoby UAL o finančování původní transakce nesprávně informovány.

YMC Tutorial: The Prague Dependency Treebank

19

Using Parallel Treebanks

- Word-based alignment
 - Phrasal alignment
 - Dictionary extraction
 - From word/phrasal alignment
 - Probabilistic
 - Machine translation
 - Statistical models
 - Evaluation/testing of systems

YMC Tutorial: The Prague Dependency Treebank

18

Habitat Domains in seabirds

- Word-based alignment
 - Phrasal alignment
 - Dictionary extraction
 - From word/phrasal alignment
 - Probabilistic
 - Machine translation
 - Statistical models
 - Evaluation/testing of systems

18

PCEDT 1.0 – The CD

- Published 2004 by the LDC (LDC2004T25)
- Texts, size of data:
 - 480,000 words: parallel annotated WSJ treebank
 - 21,600 sentences
 - 2 mil. words (53,000 sent.): Reader's Digest short stories
- Tools
 - GIZA++ (Statistical Machine Translation Toolkit)
 - Scripts for easy training ("SMT Quick Run")
 - Probabilistic dictionary (46,150 words, lemmatized)
 - Czech – English (WSJ and other sources)
- And more...

Nov. 27-28, 2006

VMC Tutorial: The Prague Dependency Treebank

21

PCEDT – some pointers

- PCEDT 1.0
 - <http://www.ldc.upenn.edu> catalog No. LDC2004T25
 - <http://ufal.mff.cuni.cz/pcedt>
- PDT 2.0 (Czech annotation - documentation)
 - <http://www.ldc.upenn.edu> catalog No. LDC2006T01
 - <http://ufal.mff.cuni.cz/pdt2.0>
- Semenky, Cinkova:
 - Constructing an English Valency Lexicon
 - <http://acl.ldc.upenn.edu/W/W06/W06-0612.pdf>

Nov. 27-28, 2006

VMC Tutorial: The Prague Dependency Treebank

22

Prague Treebanking for Everyone
Prague Arabic Dependency Treebank

Prague Arabic Dependency Treebank

PADT is a project of linguistic annotation of Modern Written Arabic based on the theory of Functional Generative Description.

Otakar Smrž

Institute of Formal and Applied Linguistics
Faculty of Mathematics and Physics
Charles University in Prague

PADT 1.0 was published in 2004 by the Linguistic Data Consortium, and has been used by tens of academic and commercial institutions.

In PADT, which now consists of the morphological and the analytical levels of description of Arabic, the annotation of **tectogrammatics** and **information structure** is being established.

Vilem Mathesius Lecture Series 21

Prague, November 29, 2006

Outline

Outline

- 1 Introduction
 - 2 Morphology
 - MorphoTrees
 - ElixirFM
 - 3 Syntax and Beyond
 - Dependency Grammar
 - Analytical Syntax
 - Tectogrammatics
 - 4 Software
 - TrEd Live
 - Encode Arabic
 - 5 References

Otakar Smrž (Charles University) Prague Arabic Dependency Treebank November 29, 2006 3 / 21

Otakar Smrž (Charles University) Prague Arabic Dependency Treebank November 29, 2006 4 / 21

Morphology Disambiguation

Arabic is a language of rich morphology, both derivational and inflectional, with highly ambiguous orthography.

String	Token	Tag	F	FUT	Buckwalter's M-Tags	Token	Form	Token	Gloss
וְהַנִּזְעָן וְהַנִּזְעָן	וְהַנִּזְעָן				S- וְהַנִּזְעָן	וְהַנִּזְעָן	וְהַנִּזְעָן	וְהַנִּזְעָן	be notif.

Boundaries of syntactic units, **tokens**, are obscure in writing—orthographical words, **strings**, consist of up to four **lexemes**.

Disambiguation encompasses subproblems like tokenization, full morphological tagging or its simplified ‘**part-of-speech**’ versions, lemmatization, diacritization or restoration of the structural components of words, plus combinations thereof.

بِكُوك	SD----MS-- DEM_PRON_MS	<u>dālikā</u>	that
عَنْ	P----- PREP	<u>an</u>	by/about
طَرِيقٍ	N-----2R NOUN+CASE_DEF_GEN	<u>ṭarīq-i</u>	way-of
الرَّسْأَلَ	N-----2D DET+NOUN+CASE_DEF_GEN	<u>ar-rasāl-i</u>	the-messages
القصيْرَةُ	A----FS2D DET+ADJ+NSUFF_FEM_SG+ +CASE_DEF_GEN	<u>al-qasīr-at-i</u>	the-short
	C----- CONJ	<u>wa-</u>	and
وَالْإِنْتَرْنِتُ	Z-----2D DET+NOUN_PROP+ +CASE_DEF_GEN	<u>al-Internet-i</u>	the-internet
	C----- CONJ	<u>wa-</u>	


MorphoTrees

Suppose you can list morphological analyses for a given input string . . .

Morphs	Form	Token	Tag	Lemma	Glosses per Morph
l ay+ (null)	~ <i>ālā</i>	VP-A-3MS--	- <i>ālā</i>	promise	/take an oath + he/it
liy~	~ <i>ālīy</i>	A-----	- <i>ālīy</i>	mechanica	/automatic
liy~+u	~ <i>ālīy-u</i>	A-----1R	- <i>ālīy</i>	mechanical	... + [def.nom.]
liy~+i	~ <i>ālīy-i</i>	A-----2R	- <i>ālīy</i>	mechanical	... + [def.gen.]
liy~+a	~ <i>ālīy-a</i>	A-----4R	- <i>ālīy</i>	mechanical	... + [def.acc.]
liy~+N	~ <i>ālīy-un</i>	A-----1I	- <i>ālīy</i>	mechanical	... + [indef.nom]
liy~+K	~ <i>ālīy-in</i>	A-----2I	- <i>ālīy</i>	mechanical	... + [indef.gen.]
l +	~ <i>āl </i>	N-----R	- <i>āl </i>	family/clan	+
+ iy	- <i>ī</i>	S-----1-S2-	- <i>ī</i>	+ my	
Iilay	<i>i lā</i>	P-----	- <i>i lā</i>	to/towards	
Iilay +	<i>i lay</i>	P-----	- <i>i lā</i>	to/towards	+
+ ya	-ya	S-----1-S2-	-ya	+ me	
Oa+liy+ (null)	<i>ālī</i>	VIIA-1-S--	- <i>waliya</i>	I + follow/come after	[ind.]
Oa+liy+a	<i>ālīy-a</i>	VIIA-1-S--	- <i>waliya</i>	I + follow/come after	[sub.]


Otakar Smrž (Charles University) Prague Arabic Dependency Treebank November 29, 2006 7 / 21

MorphoTrees



MorphoTrees

- ... organize the analyses into a hierarchy with the string as its root and the full tokens as the leaves, grouped by their lemmas, canonical forms and partitionings of the string into such forms:



ElixirFM

Morphology

ElixirFM is a high-level implementation of Functional Arabic Morphology.

ElixirEM uses the Functional Morphology library for Haskell and extends it

Morphology is modeled in terms of **paradigms**, grammatical **categories**, **lexemes** and word **classes**. The **computation** of analysis or generation is conceptually **distinguished** from the **general-purpose linguistic model**.

The lexicon of ElixirFM is derived from the open-source Buckwalter lexicon and from the **PADT** annotations. It is redesigned in important respects.


Outline

- 1 Introduction
- 2 Morphology
 - MorphoTrees
 - ElixirFM
- 3 Syntax and Beyond
 - Dependency Grammar
 - Analytical Syntax
 - Tectogrammatics
- 4 Software
 - TrEd Live
 - Encode Arabic
 - References
- 5


Dependency vs. Linearity

... by providing the basic necessities of life to its people, including medical care ...

بِوْفَدِ حَضْرُورِيَّاتِ الْحَيَاةِ الْاسَّاسِيَّةِ لِشَعْبِهَا وَمِنْ بَيْنِهَا الرَّعْيَةُ الطَّبِيعِيَّةُ




In the section on literature, the magazine presented the issue of the Arabic language and the dangers that threaten it.



Tectogrammatics

Description of linguistic meaning in its semantic and pragmatic aspects.



Outline

Buckwalter Transliteration

Software

- 1 Introduction
- 2 Morphology
 - MorphoTrees
 - ElixirFM
- 3 Syntax and Beyond
 - Dependency Grammar
 - Analytical Syntax
- 4 Software
 - TrEd Live
 - Encode Arabic
- 5 References

يُولَدُ جَمِيعُ النَّاسِ أَحْرَارًا مُتَسَاوِينَ فِي الْكَرَامَةِ وَالْحُقُوقِ. وَقَدْ وَهِبُوا عَقْلًا وَضَمِيرًا وَعَلَيْهِمْ
أَنْ يُعَامِلَ بِعَضُّهُمْ بَعْضًا بِرُوحِ الْإِخَاءِ.

yuwladu jamiyEu {ln~aAsi OaHoraArFA mutasaAwiyma fiy
{lokaraAmapi wa {loHuquwqi. waqado wnhibuwA EaqolAF
waDamiyrFA waEalayohimo Oano yuEaAmila baEoDuhmo baEoDFA
biruWhi {loIixaA,i.

يُولَدُ جَمِيعُ النَّاسِ أَحْرَارًا مُتَسَاوِينَ فِي الْكَرَامَةِ وَالْحُقُوقِ. وَقَدْ وَهِبُوا عَقْلًا وَضَمِيرًا وَعَلَيْهِمْ
أَنْ يُعَامِلَ بِعَضُّهُمْ بَعْضًا بِرُوحِ الْإِخَاءِ.

ywld jmyE AlnAs OHrArA mtsAwyn fy Alkramp wAlHqww. wqd
whbwA Eq1AwDmyrA wEllyhm On yEAml bEDhm bEDA brwH AlIxA'.

Otakar Smrk (Charles University) Prague Arabic Dependency Treebank November 29, 2006 15 / 21

Otakar Smrk (Charles University) Prague Arabic Dependency Treebank November 29, 2006 17 / 21

Notation of ArabTEX

Software

يُولَدُ جَمِيعُ النَّاسِ أَحْرَارًا مُتَسَاوِينَ فِي الْكَرَامَةِ وَالْحُقُوقِ. وَقَدْ وَهِبُوا عَقْلًا وَضَمِيرًا وَعَلَيْهِمْ
أَنْ يُعَامِلَ بِعَضُّهُمْ بَعْضًا بِرُوحِ الْإِخَاءِ.

يُولَدُ جَمِيعُ النَّاسِ أَحْرَارًا مُتَسَاوِينَ فِي الْكَرَامَةِ وَالْحُقُوقِ. وَقَدْ وَهِبُوا عَقْلًا وَضَمِيرًا وَعَلَيْهِمْ
أَنْ يُعَامِلَ بِعَضُّهُمْ بَعْضًا بِرُوحِ الْإِخَاءِ.

Yūladu ḡamī'u 'n-nāsi 'aḥrāran mutasāwīna fī 'l-karāmati wa-'l-huqūqi. Wa-qad
wuhibū aqlan wa-damīran wa-salayhim 'an yuāmila bādhuhum bādhan bi-rūḥi 'l-
'ibā'i.

\cap yUladu ^gami'u an-nasi 'a.hrArAN mutasAwIna fI
al-karAmATi wa-al-.huquQi.

\cap wa-qad wuhibU 'aqlan wa-.damIraN wa-'alayhim 'an
yu'Amila ba' .duhum ba' .dan bi-rU.hi al-'i_hA'i.

Otakar Smrk (Charles University) Prague Arabic Dependency Treebank November 29, 2006 19 / 21

Software

Encode Arabic

بِرُوحِ الْإِخَاءِ ← بِرُوحِ الْإِخَاءِ ← بِرُوحِ الْإِخَاءِ

Implemented in Perl and available on CPAN as Encode-Arabic:

```
$encoded = encode "buckwalter", decode "arabtex", $decoded  
$encoded = encode("buckwalter", decode("arabtex", $decoded))
```

Implemented in Haskell and available along with ElixirFM:

```
encoded = encode Buckwalter $ decode ArabTeX decoded  
encoded = encode Buckwalter (decode ArabTeX decoded)  
encoded = (encode Buckwalter . decode ArabTeX) decoded
```

```
[cmd] decode ArabTeX < decode.d | encode Buckwalter > encode.d
```

Otakar Smrk (Charles University) Prague Arabic Dependency Treebank November 29, 2006 18 / 21

Otakar Smrk (Charles University) Prague Arabic Dependency Treebank November 29, 2006 19 / 21

Outline

- 1 Introduction
- 2 Morphology
 - MorphoTrees
 - ElixirFM
- 3 Syntax and Beyond
 - Dependency Grammar
 - Analytical Syntax
 - Tectogrammatics
- 4 Software
 - TrEd Live
 - Encode Arabic
- 5 References

References

- Buckwalter, Tim. *Buckwalter Arabic Morphological Analyzer 1.0*. LDC catalog number LDC2002L49, ISBN 1-58563-257-0. 2002
- Forsberg, Markus and Aarne Ranta. *Functional Morphology*. Proceedings of ICFP 2004, pages 213–223. ACM Press. 2004
- Lagally, Klaus. *ArabTeX: Typesetting Arabic and Hebrew, User Manual Version 4.00*. Technical Report 2004/03, Fakultät Informatik, Universität Stuttgart. 2004
- Sgall, Petr and Eva Hajíčová and Jarmila Panevová. *The Meaning of the Sentence in Its Semantic and Pragmatic Aspects*. Academia, Prague. 1986
- Smrž, Otakar and Petr Pajas. *MorphoTrees of Arabic and Their Annotation in the TrEd Environment*. Proceedings of the NEMLAR Conference 2004, pages 38–41. 2004

PADT++ <http://ufal.mff.cuni.cz/padt/online/>

CZECH POSITIONAL MORPHOLOGICAL TAGS

1. PART OF SPEECH

- A Adjectives
- C Numerals
- D Adverbs
- I Interjection
- J Conjunction
- N Noun
- P Pronoun
- V Verb
- R Preposition
- T Particle
- X Unknown, Not Determined, Unclassifiable
- Z Punctuation (also used for the Sentence Boundary Token)

2. SUB PART OF SPEECH

- # Sentence boundary
- % Author's signature, e.g. haš-99_-B_-S
- * Word krát (lit.: "times")
- , Conjunction subordinate (incl. "aby", "kdyby" in all forms)
- } Numeral, written using Roman numerals (XIV)
- : Punctuation (except for the virtual sentence boundary word ###, which uses "Sub part of speech" #)
- = Number written using digits
- ? Numeral "kolik" (lit. "how many"/"how much")
- @ Unrecognized word form
- ^ Conjunction (connecting main clauses, not subordinate)
- 4 Relative/interrogative pronoun with adjectival declension of both types (soft and hard) ("jaký", "který", "čí", ..., lit. "what", "which", "whose", ...)
- 5 The pronoun he in forms requested after any preposition (with prefix n-: "něj", "něho", ..., lit. "him" in various cases)
- 6 Reflexive pronoun "se" in long forms ("sebe", "sobě", "sebou", lit.

"myself" / "yourself" / "herself" / "himself" in various cases; "se" is personless)

- 7 Reflexive pronouns "se" ("Case" = 4), "si" ("Case" = 3), plus the same two forms with contracted -s: "ses", "sis" (distinguished by "Person" = 2; also number is singular only) This should be done somehow more consistently, virtually any word can have this contracted -s ("cos", "polivkus", ...)
- 8 Possessive reflexive pronoun "svůj" (lit. "my"/"your"/"her"/"his" when the possessor is the subject of the sentence)
- 9 Relative pronoun "jenž", "již", ... after a preposition (n-: "něhož", "niž", ..., lit. "who")
- A Adjective, general
- B Verb, present or future form
- C Adjective, nominal (short, participial) form "rád", "schopen", ...
- D Pronoun, demonstrative ("ten", "onen", ..., lit. "this", "that", "that", ... "over there", ...)
- E Relative pronoun "což" (corresponding to English which in subordinate clauses referring to a part of the preceding text)
- F Preposition, part of; never appears isolated, always in a phrase ("nehledě (na)", "vzhledem (k)", ..., lit. "regardless", "because of")
- G Adjective derived from present transgressive form of a verb
- H Personal pronoun, clitical (short) form ("mě", "mi", "ti", "mu", ...); these forms are used in the second position in a clause (lit. "me", "you", "her", "him"), even though some of them ("mě") might be regularly used anywhere as well
- I Interjections
- J Relative pronoun "jenž", "již", ... not after a preposition (lit. "who", "whom")
- K Relative/interrogative pronoun "kdo" (lit. "who"), incl. forms with affixes -ž and -s (affixes are distinguished by the category "Variant" (for -ž) and "Person" (for -s))
- L Pronoun, indefinite "všechn", "sám" (lit. "all", "alone")
- M Adjective derived from verbal past transgressive form
- N Noun (general)
- O Pronoun "svůj", "hesvůj", "tentam" alone (lit. "own self", "not-in-mood", "gone")
- P Personal pronoun "já", "ty", "on" (lit. "I", "you", "he") (incl. forms with the enclitic -s, e.g. "tys", lit. "you're"); gender position is used for third person to distinguish "on"/"ona"/"ono" (lit. "he"/"she"/"it"), and number for all three persons
- Q Pronoun relative/interrogative "co", "copak", "cožpak" (lit. "what", "isn't-it-true-that")
- R Preposition (general, without vocalization)
- S Pronoun possessive "můj", "tvůj", "jeho" (lit. "my", "your", "his"); gender position used for third person to distinguish "jeho", "její", "jeho" (lit. "his", "her", "its"), and number for all three pronouns
- T Particle
- U Adjective possessive (with the masculine ending -uv as well as feminine -in)
- V Preposition (with vocalization -e or -u): ("ve", "pode", "ku", ..., lit. "in", "under", "to")
- W Pronoun negative ("nic", "nikdo", "nijaky", "žádný", ..., lit. "nothing", "nobody", "not-worth-mentioning", "no"/"none")
- X (temporary) Word form recognized, but tag is missing in dictionary due to delays in (asynchronous) dictionary creation
- Y Pronoun relative/interrogative co as an enclitic (after a preposition) ("oc", "nač", "zač", lit. "about what", "on"/"onto" "what", "after"/"for what")
- Z Pronoun indefinite ("nějaký", "některý", "číkoli", "cosi", ..., lit. "some", "some", "anybody's", "something")
- a Numeral, indefinite ("mnoho", "málo", "tolik", "několik", "kvólikolik", ..., lit. "much"/"many", "little"/"few", "that much"/"many", "some" ("number of"), "who-knows-how-many/much")
- b Adverb (without a possibility to form negation and degrees of comparison, e.g. "pozadu", "naplocho", ..., lit. "behind", "flatly"); i.e. both the "Negation" as well as the "Grade" attributes in the same tag are marked by - (Not applicable)
- c Conditional (of the verb "být" (lit. "to be") only) ("by", "bych", "bys", "bychom", "byste", lit. "would")
- d Numeral, generic with adjectival declension ("dvoj", "desaterý", ..., lit. "two-kinds"/..., "ten-...")
- e Verb, transgressive present (endings -e/-ě, -ic, -ice)
- f Verb, infinitive
- g Adverb (forming negation ("Negation" set to A/N) and degrees of comparison "Grade" set to 1/2/3 (comparative/superlative), e.g. "velký", "zal-jil-mal-vý", ..., lit. "big", "interesting")
- h Numeral, generic: only "jedny" and "nejedny" (lit. "one-kind"/"sort-of", "not-only-one-kind"/"sort-of")
- i Verb, imperative form
- j Numeral, generic greater than or equal to 4 used as a syntactic noun ("čtvero", "desatero", ..., lit. "four-kinds"/"sorts-of", "ten-...")

- k Numeral, generic greater than or equal to 4 used as a syntactic adjective, short form ("čtvero", ..., lit. "four-kinds"/"sorts-of")
- l Numeral, cardinal "jeden", "dva", "tři", "čtyři", "pět", ... (lit. "one", "two", "three", "four"); also "sto" and "tisíc" (lit. "hundred", "thousand") if noun declension is not used
- m Verb, past transgressive; also archaic present transgressive of perfective verbs (ex.: "udělal", lit. "(he-)having-done"; arch. also "udělaje" ("Variant" = 4), lit. "(he-)having-done")
- n Numeral, cardinal greater than or equal to 5
- o Numeral, multiplicative indefinite ("krát", lit. ("times"): "mnohokrát", "tolikrát", ..., lit. "many times", "that many times")
- p Verb, past participle, active (including forms with the enclitic -s, lit. 're' ("are"))
- q Verb, past participle, active, with the enclitic -t, lit. ("perhaps") - "could-you-imagine-that?" or "but-because-" (both archaic)
- r Numeral, ordinal (adjective declension without degrees of comparison)
- s Verb, past participle, passive (including forms with the enclitic -s, lit. 're' ("are"))
- t Verb, present or future tense, with the enclitic -t, lit. ("perhaps") - "could-you-imagine-that?" or "but-because-" (both archaic)
- u Numeral, interrogative "kolikrát", lit. "how many times?"
- v Numeral, multiplicative, definite (-krát, lit. "times": "pětkrát", ..., lit. "five times")
- w Numeral, indefinite, adjectival declension ("nejeden", "tolikrát", ..., lit. "not-only-one", "so-many-times-repeated")
- y Numeral, fraction ending at -ina; used as a noun ("pětina", lit. "one-fifth")
- z Numeral, interrogative "kolikrát", lit. "what" ("at-what-position-place-in-a-sequence")

3. GENDER

- F Feminine
- H {F, N} – Feminine or Neuter
- I Masculine inanimate
- M Masculine animate
- N Neuter
- Q Feminine (with singular only) or Neuter (with plural only); used only with participles and nominal forms of adjectives
- T Masculine inanimate or Feminine (plural only); used only with participles and nominal forms of adjectives

4. NUMBER

- D Dual, e.g. "nohama"
- P Plural, e.g. "nohami"
- S Singular, e.g. "noha"

5. CASE

- 1 Nominative, e.g. "žena"
- 2 Genitive, e.g. "ženy"
- 3 Dative, e.g. "ženě"
- 4 Accusative, e.g. "ženu"
- 5 Vocative, e.g. "ženo"
- 6 Locative, e.g. "ženě"
- 7 Instrumental, e.g. "ženou"
- X Any

6. POSSESSIVE GENDER

- F Feminine, e.g. "matčí", "její"
- M Masculine animate (adjectives only), e.g. "otců"
- X Any

7. POSSESSIVE NUMBER

- P Plural, e.g. "nás"
- S Singular, e.g. "můj"
- X Any, e.g. "your"

8. PERSON

- 1 1st person, e.g. "pišu", "pišeme"
- 2 2nd person, e.g. "píšeš", "píšete"
- 3 3rd person, e.g. "piše", "pišou"

9. TENSE

- F Future

10. GRADE

- 1 Positive, e.g. "velký"

- 2 Comparative, e.g. "větší"

- 3 Superlative, e.g. "největší"

11. NEGATION

- A Affirmative (not negated), e.g. "možný"

- N Negated, e.g. "nemožný"

12. VOICE

- A Active, e.g. "pišici"

- P Passive, e.g. "psaný"

13., 14. RESERVE 1, RESERVE 2

- Not applicable

15. VARIANT

- Basic variant, standard contemporary style; also used for standard forms allowed for use in writing by the Czech Standard Orthography Rules despite being marked there as colloquial

- 1 Variant, second most used (less frequent), still standard

- 2 Variant, rarely used, bookish, or archaic

- 3 Very archaic, also archaic + colloquial

- 4 Very archaic or bookish, but standard at the time

- 5 Colloquial, but (almost) tolerated even in public

- 6 Colloquial (standard in spoken Czech)

- 7 Colloquial (standard in spoken Czech), less frequent variant

- 8 Abbreviations

- 9 Special uses, e.g. personal pronouns after prepositions etc.

Analytical functions in PDT 2.0

Pred	predicate, a node not depending on another node; depends on #	Pnom	nominal predicate, or nom. part of predicate with copula <i>be</i>	AuxC	conjunction (subord.)	AuxK	terminal punctuation of a sentence
Sb	subject	AuxV	auxiliary verb <i>be</i>	AuxO	redundant or emotional item, 'coreferential' pronoun	ExD	a technical value for a deleted item; also for the main element of a sentence without predicate (externally-dependent)
Obj	object	Coord	coord. node	AuxZ	emphasizing word	AtrAtr	an attribute of any several preceding (syntactic) nouns
Adv	adverbial	Apos	apposition (main node)	AuxX	comma (not serving as a coordinating conjunction)	AtrAdv	structural ambiguity between adverbial and adnominal (hung on a name/noun) dependency without a semantic difference
Atv	complement (so-called determining) technically hung on a non-verbal element	AuxT	reflexive tantum	AuxG	other graphic symbols, not terminal	AdvAtr	dtto with reverse preference
AtvV	complement (so-called determining) hung on a verb, no 2 nd gov. node	AuxR	passive reflexive	AuxY	adverbs, particles not classed elsewhere	AtrObj	structural ambiguity between object and adnominal dependency without a semantic difference
Atr	attribute	AuxP	primary preposition, parts of a secondary preposition	AuxS	root of the tree (#)	ObjAtr	dtto with reverse preference

T-node attributes and their values in PDT 2.0

Notation:

attribute – attribute name
value – attribute value

A. Lexical content

t_lemma – tectogrammatical lemma
val_frame.rf – valency frame (reference to PDT-VALLEX)

B. Semantic roles and other structural relations

functor – role of the node within the t-tree structure

Functors for independent clauses:

1. **PRED** – predicate clause
2. **DENOM** – denominative clause
3. **VOCAT** – vocative clause
4. **PARTL** – interjectional clause
5. **PAR** – parenthetical clause

Actants:

6. **ACT** – actor
7. **PAT** – patient

8. **ADDR** – addressee

9. **ORIG** – origin

10. **EFF** – effect

Temporal modifiers:

11. **TWHEN** – when
12. **TFHL** – how long
13. **TFRWH** – from when
14. **THL** – how long
15. **THO** – how often
16. **TOWH** – to when
17. **TPAR** – temporal parallel
18. **TSIN** – since when

19. **TTILL** – till when

Spatial modifiers:

20. **LOC** – where
21. **DIR1** – from where
22. **DIR2** – through where
23. **DIR3** – to where
24. **AIM** – aim
25. **CAUS** – cause
26. **CNCS** – concession
27. **COND** – condition
28. **INTT** – intention

Various types of manner:

29. **ACMP** – accompaniment
30. **CPR** – comparison
31. **CRIT** – criterion
32. **DIFF** – difference
33. **EXT** – extent
34. **MANN** – manner
35. **MEANS** – means
36. **REG** – regard
37. **RESL** – result
38. **RESTR** – restriction

Specific adnominal modifiers:

39. **RSTR** – attribute
40. **APP** – appurtenance
41. **AUTH** – author
42. **MAT** – material
43. **ID** – identity

Paratactic structures:

44. **ADVS** – adversative
45. **CONFR** – confrontation
46. **CONJ** – conjunction
47. **CONTRA** – contrariety
48. **CSQ** – consequence
49. **DISJ** – disjunction
50. **GRAD** – gradation
51. **REAS** – reason
52. **APPS** – apposition
53. **CM** – coordination modifier

Multiword lexical units:

54. **CPhR** – part of complex predicate
55. **DPhR** – dependent part of an idiomatic expression

Other:

56. **COMPL** – predicative complement
57. **BEN** – benefactor
58. **CONTRD** – contradiction
59. **HER** – heritage
60. **RHEM** – rhetematizer
61. **SUBS** – substitution
62. **ATT** – attitude
63. **INTF** – intensifier
64. **MOD** – modality
65. **PREC** – reference to preceding text
66. **FPHR** – foreign language expression

subfunctor

- more detailed functor specification
1. **basic** – basic value (prototypical for the given functor)
 2. **nr** – not recognized

Values specific to spatial functors:

3. **abstr** – in abstract space
 4. **along** – along
 5. **around** – around
 6. **above** – above
 7. **behind** – behind
 8. **below** – below
 9. **betw** – between
 10. **elsew** – elsewhere
 11. **ext** – extent
 12. **front** – in front of
 13. **near** – near
 14. **opp** – opposite
 15. **target** – target
 16. **to** – to
 17. **across** – across
- Values specific to ACMP:**
18. **circ** – circumstance
 19. **incl** – inclusion
 20. **wout** – negative accompaniment (without someone)
- Values specific to CPR:**
21. **than** – difference

D. Coreference and predicative complement

coref_gram.rf – (list of) reference(s) to antecedent(s) in the sense of grammatical coreference

coref_text.rf – (list of) reference(s) to antecedent(s) in the sense of textual coreference

coref_special – special types of coreference (without obvious t-node antecedent)

1. **segm** – coreference with a sequence of preceding sentences, without more explicit limitations

2. **exoph** – antecedent not present in the text at all

compl.rf – reference to "secondary" parent t-node (in the case of "dual" complement dependency)

E. Types of t-nodes

nodetype – basic node classification

1. **root** – technical root
2. **complex** – complex node
3. **qcomplex** – quasi-complex node
4. **atom** – atomic node
5. **coap** – paratactic structure root (coordination or apposition)
6. **dphr** – dependent part of an idiomatic expression
7. **fphr** – part of a foreign-language expression
8. **list** – root node of a list structure

C. Communicative dynamism

tfa

- topic/focus articulation
1. **t** – non-contrastive contextually bound expression
 2. **f** – contextually non-bound expression

Values specific to ACMP:

3. **c** – contrastive contextually bound expression

deepord

- non-negative integer representing deep word order

a/aux.rf – (list of) reference(s) to the corresponding auxiliary a-node(s)

is_generated – distinction between nodes expressed/unexpressed in the surface form

1. **0** – surface counterpart exists
2. **1** – newly created (or "copied") node

H. Quotation and direct speech

quot/type

– type of quoted expression

1. **citation** – citation
2. **dsp** – direct speech
3. **meta** – "meta" use
4. **title** – title
5. **other** – other type

quot/set_id – id dedicated for co-indexing all nodes within a quoted expression

is_dsp_root

– root of direct speech

1. **0** – unmarked value
2. **1** – root of subtree representing direct speech

I. Other

id

– node identifier

is_name_of_person

– personal proper name

1. **0** – unmarked value
2. **1** – proper name of a person

sempos – semantic part of speech (further subdivision of complex nodes)

1. **n.denot** – denotative semantic noun

2. **n.denot.neg** – denotative semantic noun with separately represented negation

3. **n.pron.def.demon** – demonstrative definite pronominal semantic noun

4. **n.pron.def.pers** – personal definite pronominal semantic noun

5. **n.pron.indef** – indefinite pronominal semantic noun

6. **n.quant.def** – definite quantificational semantic noun

7. **adj.denot** – denotative semantic adjective

8. **adj.pron.def.demon** – demonstrative definite pronominal semantic adjective

9. **adj.pron.indef** – indefinite pronominal semantic adjective

10. **adj.quant.def** – definite quantificational semantic adjective

11. **adj.quant.indef** – indefinite quantificational semantic adjective

12. **adj.quant.grad** – gradable quantificational semantic adjective

13. **adv.denot.ngrad.nneg** – non-gradable denotative semantic adverb, impossible to negate

14. **adv.denot.ngrad.neg** – non-gradable denotative semantic adverb, possible to negate

15. **adv.denot.grad.nneg** – gradable denotative semantic adverb, impossible to negate

16. **adv.denot.grad.neg** – gradable denotative semantic adverb, possible to negate

17. **adv.pron.def** – definite pronominal semantic adverb

18. **adv.pron.indef** – indefinite pronominal semantic adverb

19. **v** – semantic verb

F. Grammatemes

sentmod – sentence modality

1. **enunc** – indicative mood
2. **excl** – exclamatory mood
3. **desid** – desiderative mood
4. **imper** – imperative mood
5. **inter** – interrogative mood

value applicable to all following grammatemes:

nr – not recognized

gram/aspect

1. **proc** – processual (counterpart to imperfective)
2. **cpl** – complex (counterpart to perfective)

gram/degcmp

– degree of comparison

1. **pos** – positive
2. **comp** – comparative
3. **acomp** – absolute comparative
4. **sup** – superlative

gram/deontmod

– deontic modality

1. **deb** – necessary
2. **hrt** – obligatory
3. **vol** – wanted/intended
4. **poss** – possible
5. **perm** – permitted
6. **fac** – ability to do something
7. **decl** – unmarked

gram/dispmod

– dispositional modality

1. **disp0** – dispositional modality absent

gram/gender

- gender
1. **anim** – masculine animate
 2. **inan** – masculine inanimate
 3. **fem** – feminine
 4. **neut** – neuter
 5. **inher** – "inherited" from antecedent

gram/indeftype

- type of (proto-) indefiniteness
1. **relat** – relative
 2. **inter** – interrogative
 3. **negat** – negative
 - 4.-10. **indef1** – **indef6** – other types of indefiniteness
 - 11.-12. **total1**, **total2** – totalizers

gram/iterativeness

– iterativeness

1. **it0** – non-iterative verb
2. **it1** – iterative verb

gram/negation

- negation
1. **neg0** – affirmative
 2. **neg1** – negative

gram/number

- number
1. **sg** – singular
 2. **pl** – plural
 3. **inher** – "inherited" from antecedent

gram/numertype

- type of numeral expression
1. **basic** – basic numeral
 2. **frac** – fractional numeral
 3. **kind** – sort numeral

G. Links to a-layer

atree.rf

– reference to the corresponding a-tree technical root (only with technical t-tree root)

a/lex.rf

– reference to (identifier of) the corresponding "autosemantic" a-node